

Package ‘Mcomp’

October 12, 2022

Version 2.8

Title Data from the M-Competitions

Description The 1001 time series from the M-competition (Makridakis et al. 1982) <[DOI:10.1002/for.3980010202](https://doi.org/10.1002/for.3980010202)> and the 3003 time series from the IJF-M3 competition (Makridakis and Hibon, 2000) <[DOI:10.1016/S0169-2070\(00\)00057-1](https://doi.org/10.1016/S0169-2070(00)00057-1)>.

Depends R (>= 2.10), forecast (>= 8.0)

Imports ggplot2

LazyData yes

LazyLoad yes

ByteCompile TRUE

License GPL-3

URL <http://pkg.robjhyndman.com/Mcomp/>,
<https://github.com/robjhyndman/Mcomp>

BugReports <https://github.com/robjhyndman/Mcomp/issues>

RoxygenNote 6.0.1.9000

NeedsCompilation no

Author Rob Hyndman [aut, cre, cph] (<<https://orcid.org/0000-0002-2140-5352>>),
Muhammad Akram [ctb],
Christoph Bergmeir [ctb] (<<https://orcid.org/0000-0002-3665-9021>>),
Mitchell O'Hara-Wild [ctb]

Maintainer Rob Hyndman <Rob.Hyndman@monash.edu>

Repository CRAN

Date/Publication 2018-06-19 04:57:55 UTC

R topics documented:

Mcomp-package	2
M1	2
M3	4

M3Forecast	5
plot.Mdata	6
subset.Mcomp	7
Index	9

Mcomp-package	<i>Data from the M-competitions</i>
---------------	-------------------------------------

Description

The 1001 time series from the M-competition (Makridakis et al. 1982), and the 3003 time series and forecasts from the IJF-M3 competition (Makridakis and Hibon, 2000).

Author(s)

Rob J Hyndman. <Rob.Hyndman@monash.edu>, with assistance from Muhammad Akram and Christoph Bergmeir.

Source

<http://forecasters.org/resources/time-series-data/m3-competition/>.

References

- Makridakis, S., A. Andersen, R. Carbone, R. Fildes, M. Hibon, R. Lewandowski, J. Newton, E. Parzen, and R. Winkler (1982) The accuracy of extrapolation (time series) methods: results of a forecasting competition. *Journal of Forecasting*, **1**, 111–153.
- Makridakis and Hibon (2000) The M3-competition: results, conclusions and implications. *International Journal of Forecasting*, **16**, 451–476.

M1	<i>M-Competition data</i>
----	---------------------------

Description

The time series from the M1 forecasting competition.

Usage

M1

Format

M1 is a list of 1001 series of class Mcomp. Each series within M1 is of class Mdata with the following structure:

sn Name of the series

st Series number and period. For example "Y1" denotes first yearly series, "Q20" denotes 20th quarterly series and so on.

n The number of observations in the time series

h The number of required forecasts

period Interval of the time series. Possible values are "YEARLY", "QUARTERLY", "MONTHLY" & "OTHER".

type The type of series. Possible values are "DEMOGR", "INDUST", "MACRO1", "MACRO2", "MICRO1", "MICRO2" & "MICRO3".

description A short description of the time series

x A time series of length n (the historical data)

xx A time series of length h (the future data)

Author(s)

Muhammad Akram and Rob Hyndman

Source

<http://forecasters.org/resources/time-series-data/m-competition/>.

References

Makridakis, S., A. Andersen, R. Carbone, R. Fildes, M. Hibon, R. Lewandowski, J. Newton, E. Parzen, and R. Winkler (1982) The accuracy of extrapolation (time series) methods: results of a forecasting competition. *Journal of Forecasting*, **1**, 111–153.

See Also

[M3](#), [subset.Mcomp](#), [plot.Mdata](#)

Examples

```
M1
plot(M1$YAF2)
subset(M1, "monthly")
```

M3

M3-Competition data

Description

The time series from the M3 forecasting competition.

Usage

M3

Format

M3 is a list of 3003 series of class Mcomp. Each series within M3 is of class Mdata with the following structure:

sn Name of the series

st Series number and period. For example "Y1" denotes first yearly series, "Q20" denotes 20th quarterly series and so on.

n The number of observations in the time series

h The number of required forecasts

period Interval of the time series. Possible values are "YEARLY", "QUARTERLY", "MONTHLY" & "OTHER".

type The type of series. Possible values for M3 are "DEMOGRAPHIC", "FINANCE", "INDUSTRY", "MACRO", "MICRO", "OTHER".

description A short description of the time series

x A time series of length n (the historical data)

xx A time series of length h (the future data)

Author(s)

Muhammad Akram and Rob Hyndman

Source

<http://forecasters.org/resources/time-series-data/m3-competition/>.

References

Makridakis and Hibon (2000) The M3-competition: results, conclusions and implications. *International Journal of Forecasting*, **16**, 451-476.

See Also

[subset.Mcomp](#), [plot.Mdata](#)

Examples

```
M3
plot(M3[[32]])
subset(M3,"monthly")
```

M3Forecast

M3-Competition forecasts of original competition participants

Description

The forecasts from all the original participating methods in the M3 forecasting competition.

Usage

```
M3Forecast
```

Format

M3Forecast is a list of data.frames. Each list element is the result of one forecasting method. The data.frame then has the following structure: Each row is the forecast of one series. Rows are named accordingly. In total there are 18 columns, i.e., 18 forecasts. If fewer forecasts than 18 exist, the row is filled up with NA values.

Author(s)

Christoph Bergmeir and Rob Hyndman

Source

<http://forecasters.org/resources/time-series-data/m3-competition/>.

References

Makridakis and Hibon (2000) The M3-competition: results, conclusions and implications. *International Journal of Forecasting*, **16**, 451-476.

Examples

```
M3Forecast[["NAIVE2"]][1,]

## Not run:
# calculate errors using the accuracy function
# from the forecast package

errors <- lapply(M3Forecast, function(f) {
  res <- NULL
  for(x in 1:length(M3)) {
```

```

    curr_f <- unlist(f[x,])
    if(any(!is.na(curr_f))) {
      curr_res <- accuracy(curr_f, M3[[x]]$xx)
    } else {
      # if no results are available create NA results
      curr_res <- accuracy(M3[[x]]$xx, M3[[x]]$xx)
      curr_res <- rep(NA, length(curr_res))
    }
    res <- rbind(res, curr_res)
  }
  rownames(res) <- NULL
  res
})

ind_yearly <- which(unlist(lapply(M3, function(x) {x$period == "YEARLY"})))
ind_quarterly <- which(unlist(lapply(M3, function(x) {x$period == "QUARTERLY"})))
ind_monthly <- which(unlist(lapply(M3, function(x) {x$period == "MONTHLY"})))
ind_other <- which(unlist(lapply(M3, function(x) {x$period == "OTHER"})))

yearly_errors <- t(as.data.frame(lapply(errors, function(x) {colMeans(x[ind_yearly,])})))
quarterly_errors <- t(as.data.frame(lapply(errors, function(x) {colMeans(x[ind_quarterly,])})))
monthly_errors <- t(as.data.frame(lapply(errors, function(x) {colMeans(x[ind_monthly,])})))
other_errors <- t(as.data.frame(lapply(errors, function(x) {colMeans(x[ind_other,])})))

yearly_errors
quarterly_errors
monthly_errors
other_errors

## End(Not run)

```

plot.Mdata

Plotting M Competition data

Description

Functions to plot a time series from the M competition data sets, showing both the training and test sections of the series.

Usage

```

## S3 method for class 'Mdata'
plot(x, xlim = c(tsp(x$x)[1], tsp(x$xx)[2]),
     ylim = range(x$x, x$xx), main = x$sn, xlab, ylab = "", ...)

## S3 method for class 'Mdata'
autoplot(object, ...)

```

Arguments

x, object	A series of M-competition data
xlim	Limits on x-axis
ylim	Limits on y-axis
main	Main title
xlab	Label on x-axis
ylab	Label on y-axis
...	Other plotting arguments passed to plot. Ignored for autoplot.

Value

autoplot.Mdata returns a ggplot2 object, while plot.Mdata returns nothing. Both functions produce a time series plot of the selected series.

Author(s)

Rob Hyndman

See Also

[M1](#), [M3](#)

Examples

```
library(ggplot2)
plot(M1[[1]])
autoplot(M1$YAF3)
autoplot(M3[["N0647"]])
```

subset.Mcomp

Subset of time series from the M Competitions

Description

subset.Mcomp returns a subset of the time series data from the M Competitions. Subsets can be for specific periods, or specific types of data or both.

Usage

```
## S3 method for class 'Mcomp'
subset(x, cond1, cond2, ...)
```

Arguments

x	M-competition data or a subset of M-competition data
cond1	Type or period of the data. Type is a character variable and period could be character or numeric.
cond2	Optional second condition specifying type or period of the data, depending on cond1. If cond1 denotes type then cond2 would denote period, but if cond1 denotes period then cond2 would denote type.
...	Other arguments.

Details

Possible values for cond1 and cond2 denoting period are 1, 4, 12, "yearly", "quarterly", "monthly" and "other".

If cond1 or cond2 equals 111, then the 111 series used in the extended comparisons in the 1982 M-competition are selected.

Possible values for cond1 and cond2 denoting type are "macro", "micro", "industry", "finance", "demographic", "allother", "macro1", "macro2", "micro1", "micro2", "micro3". These correspond to the descriptions used in the competitions. See the references for details.

Partial matching used for both conditions.

Value

An object of class Mcomp consisting of the selected series.

Author(s)

Muhammad Akram and Rob Hyndman

References

Makridakis, S., A. Andersen, R. Carbone, R. Fildes, M. Hibon, R. Lewandowski, J. Newton, E. Parzen, and R. Winkler (1982) The accuracy of extrapolation (time series) methods: results of a forecasting competition. *Journal of Forecasting*, **1**, 111–153.

Makridakis and Hibon (2000) The M3-competition: results, conclusions and implications. *International Journal of Forecasting*, **16**, 451-476.

See Also

[M1](#)

Examples

```
M3.quarterly <- subset(M3,4)
M1.yearly.industry <- subset(M1,1,"industry")
```


Index

- * **datasets**

- M1, [2](#)

- M3, [4](#)

- M3Forecast, [5](#)

- * **data**

- subset.Mcomp, [7](#)

- * **hplot**

- plot.Mdata, [6](#)

- * **package**

- Mcomp-package, [2](#)

autoplot.Mdata (plot.Mdata), [6](#)

M1, [2](#), [7](#), [8](#)

M3, [3](#), [4](#), [7](#)

M3Forecast, [5](#)

Mcomp (Mcomp-package), [2](#)

Mcomp-package, [2](#)

plot.Mdata, [3](#), [4](#), [6](#)

subset.Mcomp, [3](#), [4](#), [7](#)