

# Package ‘ThurMod’

September 19, 2023

**Type** Package

**Title** Thurstonian CFA and Thurstonian IRT Modeling

**Version** 1.1.11

**Date** 2023-09-019

**Description** Fit Thurstonian forced-choice models (CFA (simple and factor) and IRT) in R. This package allows for the analysis of item response modeling (IRT) as well as confirmatory factor analysis (CFA) in the Thurstonian framework. Currently, estimation can be performed by 'Mplus' and 'lavaan'. References:

Brown & Maydeu-Olivares (2011) <[doi:10.1177/0013164410375112](https://doi.org/10.1177/0013164410375112)>;

Jansen, M. T., & Schulze, R. (in review). The Thurstonian linked block design: Improving Thurstonian modeling for paired comparison and ranking data.;

Maydeu-Olivares & Böckenholt (2005) <[doi:10.1037/1082-989X.10.3.285](https://doi.org/10.1037/1082-989X.10.3.285)>.

**VignetteBuilder** knitr

**License** GPL (>= 3)

**Depends** R (>= 3.5.0)

**Imports** stats, utils, mvtnorm, MASS, matrixStats, lavaan

**Suggests** rmarkdown, knitr

**URL** <https://github.com/MarkusTJansen/ThurMod>

**BugReports** <https://github.com/MarkusTJansen/ThurMod/issues>

**Encoding** UTF-8

**NeedsCompilation** no

**RoxygenNote** 7.2.3

**LazyData** true

**Author** Markus Thomas Jansen [aut, cre]

(<<https://orcid.org/0000-0002-5162-4409>>)

**Maintainer** Markus Thomas Jansen <mjansen@uni-wuppertal.de>

**Repository** CRAN

**Date/Publication** 2023-09-19 16:50:02 UTC

**R topics documented:**

blocksort	2
count.combn	3
count.xblocks	4
designA	5
FC	6
FC12	6
FC_raw	7
FC_scores	7
fit.correct	8
fit.lavaan	9
fit.mplus	11
get.scores	13
get.xblocks	15
get.xblocks.any	16
i.name	17
metablock	18
mod.matrices	19
pair.combn	20
rankA	20
read.mplus	21
recode	22
redundancies	24
reliabiltyFS	25
sim.data	26
syntax.lavaan	27
syntax.mplus	29
<b>Index</b>	<b>32</b>

---

blocksort	<i>Sorts the blocks in ascending numbering</i>
-----------	--

---

**Description**

This function sorts all items in a block into ascending order.

**Usage**

```
blocksort(blocks)
```

**Arguments**

blocks	A matrix defining the blocks of the model. The number of rows must be the number of blocks, each row represents a block and contains the item numbers. The number of columns represent the number of items per block.
--------	---

**Value**

Returns a matrix consisting of the blocks where all items per blocks are sorted in ascending order.

**Examples**

```
# Define 30 items divided by ten triplets as blocks
blocks <- matrix(c(1:30), ncol = 3)

# sort the blocks
blocksort(blocks)
```

---

count.combn

*Count paired comparisons*

---

**Description**

This function calculates the number of paired comparisons needed to compare a set of N items.

**Usage**

```
count.combn(nitem)
```

**Arguments**

nitem            Number of items.

**Details**

This function is only useful, if the number of paired comparisons of a full design, that is all possible paired comparisons, is of interest. Then the number is

$$\frac{N \times (N - 1)}{2}$$

**Value**

An integer corresponding to the number of paired comparisons.

**Examples**

```
# Number of paired comparisons for a set of 15 items = 105.
count.combn(15)
```

---

 count.xblocks

*Determine the number of extra blocks*


---

### Description

This function determines the minimal number of extra blocks needed in order to link all blocks.

### Usage

```
count.xblocks(blocks)
```

### Arguments

**blocks** A matrix defining the blocks of the model. The number of rows must be the number of blocks, each row represents a block and contains the item numbers. The number of columns present the number of items per block.

### Details

The matrix of blocks must be constructed so that the number of columns corresponds to the number of items per block. The number of rows corresponds to the number of blocks for the specific measure. If  $p$  is the number of blocks, and  $k$  is the number of items per block (e.g.  $k=3$  for triplets), then the number of extra blocks can be determined by (see also Jansen & Schulze, 2023)

$$\lceil \frac{p-1}{k-1} \rceil$$

### Value

An integer corresponding to the number of extra blocks needed.

### References

Jansen, M. T., & Schulze, R. (2023). *The Thurstonian linked block design: Improving Thurstonian modeling for paired comparison and ranking data*. Manuscript submitted.

### Examples

```
# Define a matrix of blocks
blocks <- matrix(1:15,ncol=3, byrow=TRUE)

# Determine the number of extra blocks needed
count.xblocks(blocks)
```

---

designA	<i>Create the Thurstonian design matrix for paired comparison and ranking data.</i>
---------	---

---

### Description

Creates the Thurstonian design matrix for paired comparison and ranking data, given by blocks or the number of items.

### Usage

```
designA(blocks = NULL, nitems = max(unique(blocks)))
```

### Arguments

blocks	A matrix defining the blocks of the model. The number of rows must be the number of blocks, each row represents a block and contains the item numbers. The number of columns present the number of items per block.
nitems	The number of items that are included in the design.

### Details

Each Thurstonian design can be defined by blocks of at least two items. The function determines the fundamental design matrix A of the Thurstonian design, including all possible paired comparisons that can be derived by the blocks. For further information of the importance of the design matrix, see Jansen and Schulze (2023a,2023b).

### Value

Returns a design matrix which includes all paired comparisons derivable from the blocks.

### References

Jansen, M. T., & Schulze, R. (2023a). *Linear factor analytic Thurstonian forced-choice models: Current status and issues*. Manuscript submitted.

Jansen, M. T., & Schulze, R. (2023b). *The Thurstonian linked block design: Improving Thurstonian modeling for paired comparison and ranking data*. Manuscript submitted.

### Examples

```
# Define a matrix of blocks
blocks <- matrix(1:15,ncol=3, byrow=TRUE)

# Get the design matrix
loading_Matrix <- designA(blocks)
```

---

FC *Paired comparisons of \$N=15\$ items from one factor/trait (Thurstonian modeling)*

---

### Description

This data set contains synthetic data of 1000 participants on all binary indicators of 15 items. For each paired comparison, participants had to rank the two alternative items according to their preference. It is assumed that transitivity holds (that is, the data comes from a ranking task). More details can be found in Brown and Maydeu-Olivares (2011), Jansen and Schulze (2023) and Maydeu-Olivares and Böckenholt (2005).

### Usage

data(FC)

### Format

A data frame with 1000 observations on 105 variables. For a variable  $ixiy$ , the result is the response preferences between item  $x$  and item  $y$ . It is coded a 1, if item  $x$  is preferred over item  $y$ , and 0 otherwise.

### References

- Brown, A., & Maydeu-Olivares, A. (2011). Item response modeling of forced-choice questionnaires. *Educational and Psychological Measurement*, 71(3), 460-502. doi:10.1177/0013164410375112
- Jansen, M. T., & Schulze, R. (in review). *The Thurstonian linked block design: Improving Thurstonian modeling for paired comparison and ranking data.*
- Maydeu-Olivares, A., & Böckenholt, U. (2005). Structural equation modeling of paired-comparison and ranking data. *Psychological Methods*, 10(3), 285-304. doi:10.1037/1082989X.10.3.285.

---

FC12 *Paired comparisons of \$N=12\$ items from one factor/trait (Thurstonian modeling)*

---

### Description

This data set contains synthetic data of 1000 participants on all binary indicators of 12 items. For each paired comparison, participants had to rank the two alternative items according to their preference. It is assumed that transitivity holds (that is, the data comes from a ranking task). More details can be found in Brown and Maydeu-Olivares (2011), Jansen and Schulze (2023) and Maydeu-Olivares and Böckenholt (2005).

### Usage

data(FC12)

**Format**

A data frame with 1000 observations on 66 variables. For a variable  $ixiy$ , the result is the response preferences between item  $x$  and item  $y$ . It is coded a 1, if item  $x$  is preferred over item  $y$ , and 0 otherwise.

**References**

- Brown, A., & Maydeu-Olivares, A. (2011). Item response modeling of forced-choice questionnaires. *Educational and Psychological Measurement*, 71(3), 460-502. doi:10.1177/0013164410375112
- Jansen, M. T., & Schulze, R. (in review). *The Thurstonian linked block design: Improving Thurstonian modeling for paired comparison and ranking data*.
- Maydeu-Olivares, A., & Böckenholt, U. (2005). Structural equation modeling of paired-comparison and ranking data. *Psychological Methods*, 10(3), 285-304. doi:10.1037/1082989X.10.3.285.

---

FC_raw	<i>Raw ranking data of \$N=15\$ items from three factors/traits (Thurstonian modeling)</i>
--------	--

---

**Description**

This data set contains synthetic raw data of 1000 participants on a ranking task on 15 items.

**Usage**

```
data(FC_raw)
```

**Format**

A data frame with 1000 observations on 15 variables.

---

FC_scores	<i>Scores of the data set 'FC' from Mplus.</i>
-----------	--

---

**Description**

This data set contains synthetic data of 1000 participants on all binary indicators of 15 items and their factor scores. For each paired comparison, participants had to rank the two alternative items according to their preference. It is assumed that transitivity holds (that is, the data comes from a ranking task). More details can be found in Brown and Maydeu-Olivares (2011), Jansen and Schulze (2023) and Maydeu-Olivares and Böckenholt (2005).

**Usage**

```
data(FC_scores)
```

**Format**

A data frame with 1000 observations on 111 variables. For a variable  $ixiy$ , the result is the response preferences between item  $x$  and item  $y$ . It is coded a 1, if item  $x$  is preferred over item  $y$ , and 0 otherwise. The last six variables are the resulting factor scores and the standard error of factor scores for three factors.

**References**

- Brown, A., & Maydeu-Olivares, A. (2011). Item response modeling of forced-choice questionnaires. *Educational and Psychological Measurement*, 71(3), 460-502. doi:10.1177/0013164410375112
- Jansen, M. T., & Schulze, R. (in review). *The Thurstonian linked block design: Improving Thurstonian modeling for paired comparison and ranking data.*
- Maydeu-Olivares, A., & Böckenholt, U. (2005). Structural equation modeling of paired-comparison and ranking data. *Psychological Methods*, 10(3), 285-304. doi:10.1037/1082989X.10.3.285.

---

fit.correct	<i>Correct degree of freedom and fit indices in Thurstonian block models</i>
-------------	--

---

**Description**

Correct fit indices (RMSEA and CFI) by correcting the degrees of freedom after estimation a Thurstonian model.

**Usage**

```
fit.correct(n, blocks, chi2_mod, df_mod, chi2_base, df_base)
```

**Arguments**

n	The number of respondents.
blocks	A matrix defining the blocks of the model. The number of rows must be the number of blocks, each row represents a block and contains the item numbers. The number of columns present the number of items per block.
chi2_mod	The $\chi^2$ value of the estimated model.
df_mod	The degrees of freedom of the estimated model.
chi2_base	The $\chi^2$ value of the baseline model.
df_base	The degrees of freedom of the baseline model.

**Details**

If a ranking design is used (variances of binary indicators is zero) there are redundancies among the thresholds and tetrachoric correlations to be estimated. This is the case, whenever the number of items per block is larger than two. In these cases the degrees of freedom must be corrected by subtracting the redundancies. For more details see Jansen and Schulze (2023) and Maydeu-Olivares (1999).



**Value**

Returns a vector containing corrected degrees of freedom, and the corrected RMSEA and CFI values.

**References**

Jansen, M. T., & Schulze, R. (in review). *The Thurstonian linked block design: Improving Thurstonian modeling for paired comparison and ranking data.*

Maydeu-Olivares, A. (1999). Thurstonian modeling of ranking data via mean and covariance structure analysis. *Psychometrika*, 64(3), 325-340. doi:10.1007/BF02294299

**Examples**

```
# Define 30 items divided by ten triplets as blocks
blocks <- matrix(c(1:30), ncol = 3)

# Assume the model yield the following fit, with 426 respondents
# chi2_mod = 224.456, df_mod = 59, chi2_base = 1056.566, df_base = 90

fit.correct(426,blocks,224.456,59,1056.566,90)

# The corrected values are rmsea = 0.0917892; cfi = 0.8184749
```

---

fit.lavaan

*Performs lavaan estimation of the given model.*


---

**Description**

This function writes a lavaan syntax given the specifications of the Thurstonian forced choice model. Additionally it runs the code (given lavaan is installed) and returns the results.

**Usage**

```
fit.lavaan(blocks, itf, model, data = NULL, estimator = "ULSMV",
  rename_list = NULL)
```

**Arguments**

blocks	A matrix defining the blocks of the model. The number of rows must be the number of blocks, each row represents a block and contains the item numbers. The number of columns present the number of items per block.
itf	A vector defining the items-to-factor relation. For example 'c(1,1,1,2,2,2)' defines six items, the first three correspond to factor 1, the second three correspond to factor 2.

model	A descriptor for the model. Can be one of ‘lmean’, ‘uc’, ‘irt’ or ‘simple2’, ‘simple3’ or ‘simple5’. The Number behind the ‘simple’ statement defines the Thurstone case.
data	A matrix or data frame including the binary indicators as columns and respondents as rows.
estimator	Which estimator should be used? All estimators that are available in ‘lavaan’ can be used. Defaults to ‘ULSMV’.
rename_list	A list with two vectors to rename the objects in the syntax. Vector one is the original names, vector two the new names. Defaults to ‘NULL’.

### Details

The syntax currently is able to perform model analysis for the latent utility model (‘simple’ and ‘lmean’; Maydeu-Olivares & Böckenholt, 2005) the unconstrained factor model (‘uc’; Maydeu-Olivares & Böckenholt, 2005) and the IRT model(‘irt’; Maydeu-Olivares & Brown, 2010). Additionally, all model types can be performed with all types of forced choice designs (full, block, partially linked block, linked block). For an overview and review see Jansen and Schulze (2023a,2023b).

The standard naming procedure *ixiy*, for the comparison of items *x* and *y*, can be changed by specifying the ‘rename\_list’ argument. The first vector of the should be the vector of original names, for example ‘c(‘i1i2’,‘i1i3’,‘i2i3’,‘Trait1’,‘Trait2’,‘Trait3’)’ the second vector should contain the new names, for example ‘c(‘A01E12’,‘A01C13’,‘E01C23’,‘Agree’,‘Extra’,‘Consc’)’.

### Value

Returns a lavaan object containing the specified results, after model analysis.

### References

- Maydeu-Olivares, A., & Böckenholt, U. (2005). Structural equation modeling of paired-comparison and ranking data. *Psychological Methods*, *10*(3), 285-304. doi:10.1037/1082989X.10.3.285
- Maydeu-Olivares, A., & Brown, A. (2010). Item response modeling of paired comparison and ranking data. *Multivariate Behavioural Research*, *45*(6), 935-974. doi:10.1080/00273171.2010.531231
- Jansen, M. T., & Schulze, R. (2023a). *Linear factor analytic Thurstonian forced-choice models: Current status and issues*. Educational and Psychological Measurement.
- Jansen, M. T., & Schulze, R. (2023b, in review). *The Thurstonian linked block design: Improving Thurstonian modeling for paired comparison and ranking data*.

### Examples

```
# read and save data set FC
data(FC12)

# set seed and define blocks
blocks <- matrix(c(5,2,1,4,7,6,3,8,10,12,9,11), ncol = 3)

# define the item-to-factor relation
itf <- rep(1:3,4)
```

```
# Create and run syntax
fit <- fit.lavaan(blocks, itf, 'irt', FC, estimator = 'ULSMV')
```

---

fit.mplus	<i>Performs Mplus estimation of the given model.</i>
-----------	--

---

## Description

This function writes the Mplus syntax given the specifications of a Thurstonian forced choice design. Additionally it runs the code (given Mplus is installed) and returns the results.

## Usage

```
fit.mplus(blocks, itf, model, input_path, output_path = NULL,
  data_path = "myDataFile.dat", fscore_path = "myFactorScores.dat",
  title = "myFC_model", ID = FALSE, byblock = TRUE,
  estimator = "ULSMV", data_full = FALSE, standardized = TRUE,
  rename_list = NULL, ...)
```

## Arguments

blocks	A matrix defining the blocks of the model. The number of rows must be the number of blocks, each row represents a block and contains the item numbers. The number of columns present the number of items per block.
itf	A vector defining the items-to-factor relation. For example 'c(1,1,1,2,2,2)' defines six items, the first three correspond to factor 1, the second three correspond to factor 2.
model	A descriptor for the model. Can be one of 'lmean', 'uc', 'irt' or 'simple2', 'simple3' or 'simple5'. The Number behind the 'simple' statement defines the Thurstone case.
input_path	Path to save the Mplus input file. Defaults to 'myFC_model.inp'.
output_path	Path to the Mplus output file. Defaults to 'myFC_model.out'.
data_path	Path of the data file for Mplus. Defaults to 'myDataFile.dat'.
fscore_path	Path to save the file of factor scores. Defaults to 'myFactorScores.dat'.
title	Title of the Mplus model. Defaults to 'myFC_model'.
ID	Logical. Should a ID variable be included? The ID must be the first variable in the data set. Defaults to 'FALSE'.
byblock	Logical. Should the order in Mplus variable statement be the same as in the blocks. Defaults to 'TRUE'.
estimator	Which estimator should be used? All Estimators that are available in Mplus can be used. Defaults to 'ULSMV'.
data_full	Logical. Are the data considered to be from a full design? Defaults to 'FALSE'.

standardized	Logical. Should standardized values be computed? Defaults to 'TRUE'.
rename_list	A list with two vectors to rename the objects in the syntax. Vector one is the original names, vector two the new names. Defaults to 'NULL'.
...	Further arguments passed to function 'read.mplus'.

### Details

The syntax currently is able to perform model analysis for the latent utility models ('simple' and 'lmean'; Maydeu-Olivares & Böckenholt, 2005) the unconstrained factor model ('uc'; Maydeu-Olivares & Böckenholt, 2005) and the IRT model('irt'; Maydeu-Olivares & Brown, 2010). Additionally, all model types can be performed with all types of forced choice designs (full, block, partially linked block, linked block). For an overview and review see Jansen and Schulze (2023a,2023b).

The function writes and saves the Mplus input files, keeps the output files and reads the results specified for the function 'read.mplus'.

The standard naming procedure *ixiy*, for the comparison of items *x* and *y*, can be changed by specifying the 'rename\_list' argument. The first vector of the should be the vector of original names, for example 'c('i1i2','i1i3','i2i3','Trait1','Trait2','Trait3')' the second vector should contain the new names, for example 'c('A01E12','A01C13','E01C23','Agree','Extra','Consc')'.

### Value

Returns a list containing the specified results, after model analysis.

### References

Maydeu-Olivares, A., & Böckenholt, U. (2005). Structural equation modeling of paired-comparison and ranking data. *Psychological Methods*, *10*(3), 285-304. doi:10.1037/1082989X.10.3.285

Maydeu-Olivares, A., & Brown, A. (2010). Item response modeling of paired comparison and ranking data. *Multivariate Behavioural Research*, *45*(6), 935-974. doi:10.1080/00273171.2010.531231

Jansen, M. T., & Schulze, R. (2023a). *Linear factor analytic Thurstonian forced-choice models: Current status and issues*. Educational and Psychological Measurement.

Jansen, M. T., & Schulze, R. (2023b, in review). *The Thurstonian linked block design: Improving Thurstonian modeling for paired comparison and ranking data*.

### Examples

```
# read and save data set FC
data(FC)
write.table(FC,paste0(tempdir(),'/','my_data.dat'),quote=FALSE, sep=" ",
col.names = FALSE, row.names = FALSE)

# set seed and define blocks
set.seed(1)
blocks <- matrix(sample(1:15,15), ncol = 3)

# define the item-to-factor relation
itf <- rep(1:3,5)
```

```
# perform analysis
## Not run:
fit.mplus(blocksort(blocks),itf,'irt',data_path = 'mydata.dat', data_full = TRUE,
input_path = paste0(tempdir(), '/', 'myFC_model'))

## End(Not run)
```

---

get.scores

*Estimate factor scores based on Genuine Likelihood*


---

### Description

This function estimates factor scores based on genuine likelihood (Yousfi, 2019).

### Usage

```
get.scores(dat, blocks, itf, fit, alg = mvtnorm::TVPACK(), log = TRUE, mp,
  sp, serr = TRUE, sv = NULL, blocks_ul = NULL, mplus = FALSE, ...)
```

### Arguments

dat	A data.frame or matrix defining holding the binary coded and named response data.
blocks	A matrix defining the blocks of the model. The number of rows must be the number of blocks, each row represents a block and contains the item numbers. The number of columns present the number of items per block.
itf	A vector defining the items-to-factor relation. For example 'c(1,1,1,2,2,2)' defines six items, the first three correspond to factor 1, the second three correspond to factor 2.
fit	The fit object. In case of Mplus, this is the path to the Mplus output file. In case of lavaan this is the lavaan Object.
alg	The algorithm to use for numerical integration. See ?mvtnorm::pmvnorm.
log	logical. Should the log transformed results be returned. Defaults to TRUE.
mp	The means of prior distribution. Defaults to multivariate normal with means 0 and vars 1
sp	The vars of prior distribution. Defaults to multivariate normal with means 0 and vars 1
serr	Logical. Should the standard errors be returned. Defaults to TRUE.
sv	Starting values. Defaults to NULL.
blocks_ul	Similar to 'blocks', but only with the unlinked design. Useful for comparison with other functions based on R.
mplus	Logical. Are results read from mplus? Defaults to FALSE.
...	other arguments passed by get.scores for optim.

## Details

The function estimates factor scores based on the Thurstonian IRT model and based on genuine likelihood proposed by Yousfi (2019). The function allows for the estimation of factor scores under all block designs, limited only by numerical integration procedures. For items per block between 5 and 20 use 'alg=mvtnorm::Miwa()'. Additionally, all model types can be performed with all types of forced choice designs (full, block, partially linked block, linked block). For an overview and review see Jansen and Schulze (2023a,2023b).

The standard naming procedure `ixiy`, for the comparison of items `x` and `y`.

## Value

The result is a list with the factor scores and the standard errors per person and factor.

## References

- Maydeu-Olivares, A., & Böckenholt, U. (2005). Structural equation modeling of paired-comparison and ranking data. *Psychological Methods*, *10*(3), 285-304. doi:10.1037/1082989X.10.3.285
- Maydeu-Olivares, A., & Brown, A. (2010). Item response modeling of paired comparison and ranking data. *Multivariate Behavioural Research*, *45*(6), 935-974. doi:10.1080/00273171.2010.531231
- Jansen, M. T., & Schulze, R. (2023a). *Linear factor analytic Thurstonian forced-choice models: Current status and issues*. Educational and Psychological Measurement.
- Jansen, M. T., & Schulze, R. (2023b, in review). *The Thurstonian linked block design: Improving Thurstonian modeling for paired comparison and ranking data*.
- Yousfi, S. (2019). Person Parameter Estimation for IRT Models of Forced-Choice Data: Merits and Perils of Pseudo-Likelihood Approaches. In: Wiberg, M., Molenaar, D., González, J., Böckenholt, U., Kim, JS. (eds) *Quantitative Psychology*. IMPS 2019. Springer Proceedings in Mathematics & Statistics, vol 322. Springer, Cham. doi:10.1007/9783030434694\_3.

## Examples

```
# read and save data set FC
data(FC12)

# set seed and define blocks
blocks <- matrix(c(5,2,1,4,7,6,3,8,10,12,9,11), ncol = 3)

# define the item-to-factor relation
itf <- rep(1:3,4)

# Create and run syntax
fit <- fit.lavaan(blocks, itf, 'irt', FC, estimator = 'ULSMV')

# get scores for the first two respondents
ests <- get.scores(dat=as.matrix(FC)[1:2,],itf=itf, blocks=blocks,
fit = fit,mp=rep(0,max(itf)),
sp=diag(1,max(itf)),estimator="MAP",sv=NULL, alg=mvtnorm::Miwa(),log=TRUE, mplus=FALSE)
```

---

`get.xblocks`*Get extra blocks in a Thurstonian design, that links all blocks.*

---

### Description

The function creates extra blocks for a Thurstonian design, that links all initial blocks with as few extra blocks as possible. The number of extra blocks is determined by ‘count.xblocks’ (see Jansen & Schulze, 2023).

### Usage

```
get.xblocks(blocks, itf, multidim, item_not = NULL, min = FALSE,
            show.warnings = FALSE)
```

### Arguments

<code>blocks</code>	A matrix defining the blocks of the model. The number of rows must be the number of blocks, each row represents a block and contains the item numbers. The number of columns present the number of items per block.
<code>itf</code>	A vector defining the items-to-factor relation. For example ‘c(1,1,1,2,2,2)’ defines six items, the first three correspond to factor 1, the second three correspond to factor 2.
<code>multidim</code>	Logical. Should the items within each linking block be forced to be multidimensional?
<code>item_not</code>	The items that are differently keyed compared to the majority of items.
<code>min</code>	Logical. Should a minimal number of blocks contain mixed keyed items?
<code>show.warnings</code>	Logical. Should warnings be shown?

### Value

The result is a matrix where the rows correspond to the specific extra blocks.

### References

Jansen, M. T., & Schulze, R. (2023). *The Thurstonian linked block design: Improving Thurstonian modeling for paired comparison and ranking data*. Manuscript submitted.

### Examples

```
# Define a matrix of blocks
blocks <- matrix(1:15,ncol=3, byrow=TRUE)

# define the item-to-factor relation
itf <- rep(1:3,5)

# Get the extra blocks for a completely linked design
```

```
get.xblocks(blocks, itf, FALSE)
```

---

<code>get.xblocks.any</code>	<i>Get extra blocks in a Thurstonian design, that links as few blocks as possible.</i>
------------------------------	--

---

### Description

The function creates extra blocks in a Thurstonian design, that links as few initial blocks as possible, with the number of blocks determined by ‘count.xblocks’. This is only useful for comparisons between linked and partially linked block designs (Jansen & Schulze, 2023).

### Usage

```
get.xblocks.any(blocks, itf, multidim)
```

### Arguments

<code>blocks</code>	A matrix defining the blocks of the model. The number of rows must be the number of blocks, each row represents a block and contains the item numbers. The number of columns present the number of items per block.
<code>itf</code>	A vector defining the items-to-factor relation. For example ‘c(1,1,1,2,2,2)’ defines six items, the first three correspond to factor 1, the second three correspond to factor 2.
<code>multidim</code>	Logical. Should the items within each linking block be forced to be multidimensional?

### Details

The main strategy of the function is to create extra blocks that link as few blocks as possible, with the number of blocks determined by ‘count.xblocks’. Therefore, first all combinations of additional blocks with the first two blocks are created. If more extra blocks are needed the function uses block three, four, etc..

### Value

The result is a matrix where the rows correspond to the specific extra blocks.

### References

Jansen, M. T., & Schulze, R. (2023). *The Thurstonian linked block design: Improving Thurstonian modeling for paired comparison and ranking data*. Manuscript submitted.



## Examples

```
# Define a matrix of blocks
blocks <- matrix(1:15,ncol=3, byrow=TRUE)

# define the item-to-factor relation
itf <- rep(1:3,5)

# Get the extra blocks for a partially linked design
get.xblocks.any(blocks, itf, FALSE)
```

---

i.name	<i>Creates names for paired comparisons of a given design.</i>
--------	--

---

## Description

This function creates names for paired comparisons in the *ixiy* scheme. If items 1 and 2 are compared, this corresponds to *ili2*.

## Usage

```
i.name(blocks)
```

## Arguments

blocks	A matrix defining the blocks of the model. The number of rows must be the number of blocks, each row represents a block and contains the item numbers. The number of columns present the number of items per block.
--------	---

## Value

Returns a character vector, containing names for all binary indicators of a design.

## Examples

```
# Define 30 items divided by ten triplets as blocks
blocks <- matrix(c(1:30), ncol = 3)

i.name(blocks)
```

---

metablock	<i>Find all general blocks</i>
-----------	--------------------------------

---

## Description

This function creates meta interlinked blocks within a Thurstonian design.

## Usage

```
metablock(blocks)
```

## Arguments

**blocks** A matrix defining the blocks of the model. The number of rows must be the number of blocks, each row represents a block and contains the item numbers. The number of columns present the number of items per block.

## Details

This function creates meta interlinked blocks of a block design. These are blocks, that have at least one link from each of its items to any other of its items. If there is not such a link between every item, there are at least two meta blocks.

## Value

Returns a list of items that form meta interlinked blocks.

## Examples

```
# Define 30 items divided by ten triplets as blocks
blocks <- matrix(c(1:30), ncol = 3)

# Add one block to link the first three blocks.
blocks <- rbind(blocks,c(1,2,3))

# Find meta blocks
metablock(blocks)
```

---

mod.matrices	<i>Create model matrices for Thurstonian modeling</i>
--------------	---

---

**Description**

This function creates and returns model matrices of Thurstonian model equations.

**Usage**

```
mod.matrices(blocks, itf, model)
```

**Arguments**

blocks	A matrix defining the blocks of the model. The number of rows must be the number of blocks, each row represents a block and contains the item numbers. The number of columns present the number of items per block.
itf	A vector defining the items-to-factor relation. For example 'c(1,1,1,2,2,2)' defines six items, the first three correspond to factor 1, the second three correspond to factor 2.
model	A descriptor for the model. Can be one of 'lmean', 'uc', 'irt' or 'simple2', 'simple3' or 'simple5'. The Number behind the 'simple' statement defines the Thurstone case.

**Value**

Returns a list of elements containing model matrix information.

**Examples**

```
# set seed and define blocks
set.seed(1)
blocks <- matrix(sample(1:15,15), ncol = 3)

# define the item-to-factor relation
itf <- rep(1:3,5)

mod.matrices(blocks,itf,'irt')
```

---

pair.combn	<i>Determine all paired comparisons</i>
------------	---

---

**Description**

This function returns a matrix containing all paired comparisons defined by a design.

**Usage**

```
pair.combn(blocks, unique = TRUE)
```

**Arguments**

blocks	A matrix defining the blocks of the model. The number of rows must be the number of blocks, each row represents a block and contains the item numbers. The number of columns present the number of items per block.
unique	Logical. Should only unique paired comparisons be returned?

**Value**

Returns a matrix with all paired comparisons defined by a design.

**Examples**

```
#' # Define 30 items divided by three triplets as blocks
blocks <- matrix(c(1:30), ncol = 3)

# Get all blocks
pair.combn(blocks)
```

---

rankA	<i>Determine the rank of the design matrix defined by the blocks.</i>
-------	---

---

**Description**

This function determines the rank of the fundamental design matrix defined by the blocks.

**Usage**

```
rankA(blocks)
```

**Arguments**

blocks	A matrix defining the blocks of the model. The number of rows must be the number of blocks, each row represents a block and contains the item numbers. The number of columns present the number of items per block.
--------	---

**Value**

Returns the rank of the design matrix as an integer.

**Examples**

```
# Define nine items divided by three triplets as blocks
blocks <- matrix(c(1:9), ncol = 3)

# Determine the rank of the design matrix
rankA(blocks)
```

---

read.mplus	<i>Reads results from Mplus output file.</i>
------------	--

---

**Description**

This function reads and returns results from an Mplus output file.

**Usage**

```
read.mplus(blocks, itf, model, output_path, convergence = TRUE,
  fit.stat = TRUE, loading = TRUE, cor = TRUE, intercept = TRUE,
  threshold = TRUE, resvar = TRUE, standardized = FALSE)
```

**Arguments**

blocks	A matrix defining the blocks of the model. The number of rows must be the number of blocks, each row represents a block and contains the item numbers. The number of columns present the number of items per block.
itf	A vector defining the items-to-factor relation. For example 'c(1,1,1,2,2,2)' defines six items, the first three correspond to factor 1, the second three correspond to factor 2.
model	A descriptor for the model. Can be one of 'lmean', 'uc', 'irt' or 'simple2', 'simple3' or 'simple5'. The Number behind the 'simple' statement defines the Thurstone case.
output_path	Path to the Mplus output file. Defaults to 'myFC_model.out'.
convergence	Logical. Should a message for convergence be returned? Defaults to 'TRUE'.
fit.stat	Logical. Should fit statistics be returned? Defaults to 'TRUE'.
loading	Logical. Should loading estimates be returned? Defaults to 'TRUE'.
cor	Logical. Should latent correlation estimates be returned? Defaults to 'TRUE'.
intercept	Logical. Should intercepts be returned? Does only work for 'model = 'lmean''. Defaults to 'TRUE'.

threshold Logical. Should thresholds be returned? Does only work for 'model = 'uc'' or 'irt'. Defaults to 'TRUE'.

resvar Logical. Should residual variances be returned? Defaults to 'TRUE'.

standardized Logical. Should standardized values be returned? Defaults to 'FALSE'.

### Value

Returns a list containing the specified results, after model analysis, by reading the results from the 'output\_path'.

### Examples

```
# read and save data set FC
data(FC)

write.table(FC,paste0(tempdir(),'/','my_data.dat'),quote=FALSE, sep=" ",
col.names = FALSE, row.names = FALSE)

# set seed and define blocks
set.seed(1)
blocks <- matrix(sample(1:15,15), ncol = 3)

# define the item-to-factor relation
itf <- rep(1:3,5)

# perform analysis
## Not run:
fit.mplus(blocksort(blocks),itf,'irt',data_path = 'mydata.dat', data_full = TRUE,
input_path = paste0(tempdir(),'/','myFC_model'))

# After estimation
read.mplus(blocks,itf,'irt',output_path = paste0(tempdir(),'/','myFC_model.out'))

## End(Not run)
```

---

recode

*Recode variables.*

---

### Description

Recode variables.

### Usage

```
recode(var = var, vals = c(1, 2, 3, 4, 5), ct = c(5, 4, 3, 2, 1),
cat = FALSE)
```

**Arguments**

<code>var</code>	A variable/column of a data matrix/ data frame containing data to be recoded.
<code>vals</code>	A vector containing the original scores. If <code>cat</code> is TRUE, these are thresholds.
<code>ct</code>	A vector containing the desired scores.
<code>cat</code>	Logical. should the data be categorized? ### Outputs —

**Details**

This function is a simple recode function. It is possible to recode any value to any other value, as long as the class of values within a vector are equal. If an interval of numerical values should be categorized, for N categories, N-1 thresholds must be given. The first N-1 categories are constructed by using all values that are smaller or equal ( $\leq$ ) than the thresholds, the last category is constructed to be all values larger than the last threshold.

**Value**

Returns a vector with the recoded input values.

**Author(s)**

Markus Thomas Jansen

**Examples**

```
#numerical
v <- rep(c(1:5),10)
v_r <- recode(v, c(1:5), c(5:1))

# character
v <- rep(c('a','b','d','e'),10)
v_r <- recode(v, c('a','b','d','e'), c('apple','1','dummy',TRUE))

# interval
set.seed(1)
v <- sample(runif(20,0,6))

# recode x <= 1.3 into 1
# recode x <= 2.6 into 2
# recode x <= 3.9 into 3
# recode x <= 5.2 into 4
# recode x > 5.1 into 5
v_r <- recode(v,c(1.3,2.6,3.9,5.2),c(1:5),cat=TRUE)
```

---

redundancies	<i>Determine the number of redundancies</i>
--------------	---

---

### Description

This function determines the number of redundancies among the tetrachoric correlations and thresholds.

### Usage

```
redundancies(blocks, warn = TRUE)
```

### Arguments

blocks	A matrix defining the blocks of the model. The number of rows must be the number of blocks, each row represents a block and contains the item numbers. The number of columns present the number of items per block.
warn	Logical. Should warning messages be returned? Defaults to 'TRUE'.

### Details

If a ranking design is used (variances of binary indicators is zero) there are redundancies among the thresholds and tetrachoric correlations to be estimated. This is the case, whenever the number of items per block is larger than two. In these cases the degrees of freedom must be corrected by subtracting the redundancies. For more details see Jansen and Schulze (2023) and Maydeu-Olivares (1999).

### Value

Returns an integer of the number of redundancies.

### References

Jansen, M. T., & Schulze, R. (in review). *The Thurstonian linked block design: Improving Thurstonian modeling for paired comparison and ranking data*.

Maydeu-Olivares, A. (1999). Thurstonian modeling of ranking data via mean and covariance structure analysis. *Psychometrika*, 64(3), 325-340. doi:10.1007/BF02294299

### Examples

```
# Define 30 items divided by ten triplets as blocks
blocks <- matrix(c(1:30), ncol = 3)

# define the item-to-factor relation
itf <- rep(1:3,10)

# Determine the redundancies
```



redundancies(blocks)

---

reliabiltyFS      *Calculate reliability estimate for factor scores.*

---

### Description

This function returns a reliability estimate for factor scores estimated via the Thurstonian IRT models.

### Usage

```
reliabiltyFS(scores, scores_se, method = "sub")
```

### Arguments

scores	A matrix with factor scores. Rows are respondents, columns are factors/traits.
scores_se	A matrix with the standard errors of the factor scores. Rows are respondents, columns are factors/traits. Factors/traits must be in the same order as for 'scores'.
method	Can be one of 'div' or 'sub'. See details. Defaults to 'sub'.

### Details

The function returns the empirical reliability of factor scores. If  $\sigma^2$  is the sample variance of the estimated scores and  $\overline{\sigma_{error}^2}$  is the average if the squared scores, that is

$$\overline{\sigma_{error}^2} = \frac{1}{N} \sum_i^N = 1se_{scores}^2$$

then the subtraction method, a classical reliability estimate similar to classical test theory is returned using 'sub' yields

$$\frac{\sigma^2 - \overline{\sigma_{error}^2}}{\sigma^2}$$

for the reliability of the scores. If 'div' is chosen, and alternative division based approach is used.

$$\frac{\sigma^2}{\sigma^2 + \overline{\sigma_{error}^2}}$$

If 'irt' is chosen, a plot returning the standard error of the scores with the scores is returned per factor.

### Value

Returns the reliability value. If method = 'irt', the a plot with the reliability depending on the factorscore is returned.

## Examples

```
# read and save data set FC
data(FC_scores)

# get reliability
reliabiltyFS(FC_scores[,c(106,108,110)],FC_scores[,c(107,109,111)])
```

---

 sim.data

---

*Create data based on Thurstonian model equations*


---

## Description

Simulates a data set of paired comparisons or ranking data based a Thurstonian latent utility model.

## Usage

```
sim.data(nfactor = 1, nitem, nperson, itf, model = "factor",
  variables = NULL, ints = NULL, lmu = NULL, ivarcov = NULL,
  loadings = NULL, varcov = NULL, graded = FALSE, ncat = NULL,
  thres = NULL, transitive = TRUE, var = 0, fvalues = FALSE,
  sim = TRUE)
```

## Arguments

nfactor	The number of factors. Defaults to 1.
nitem	The number of items.
nperson	The number of data points (= respondents) to simulate.
itf	A vector defining the items-to-factor relation. For example 'c(1,1,1,2,2,2)' defines six items, the first three correspond to factor 1, the second three correspond to factor 2.
model	The model class from which to simulate. Options are 'simple', 'factor', 'uc' and 'irt'. Defaults to 'factor'.
variables	A vector containing the names of paired comparison variables to return. If 'NULL' (default), all variables are returned.
ints	A vector defining the latent intercepts of item pairs.
lmu	A vector defining the latent means of items.
ivarcov	A matrix defining the variance-covariance matrix of the items.
loadings	A vector defining the loadings of items.
varcov	A matrix defining the variance-covariance matrix of the traits.
graded	Logical. Should a graded preference model be simulated? Defaults to 'FALSE'.
ncat	Numerical. The number of categories to specify for graded preference models. If graded = 'FALSE', ncat is 2.

thres	A vector of thresholds to categorize the latent difference response. If no thresholds are given, they are simulated from the distribution of the latent items. If <code>graded = 'FALSE'</code> , the thresholds are all 0.
transitive	Logical. Should the data be transitive? If <code>'TRUE'</code> , ranking data is simulated, else paired comparison data is simulated. Defaults to <code>'TRUE'</code> .
var	A vector containing the variances for each paired comparison. Defaults to 0.
fvalues	Logical. Should simulated factor values be returned? Defaults to <code>'FALSE'</code> .
sim	Logical. Should the simulated data be returned? Defaults to <code>'TRUE'</code> .

### Details

The syntax currently is able to simulate data from the latent utility model (`'simple'` and `'factor'`; Maydeu-Olivares & Böckenholt, 2005) the unconstrained factor model (`'uc'`; Maydeu-Olivares & Böckenholt, 2005) and the IRT model (`'irt'`; Maydeu-Olivares & Brown, 2010).

### Value

Returns a list containing the true factor scores and the data, or a matrix containing the data.

### Examples

```
nfactor <- 3
nitem <- 15
nperson <- 1000
itf <- rep(1:3,5)
varcov <- diag(1,3)

# latent utility means
set.seed(69)
lmu <- runif(nitem, -1, 1)
loadings <- runif(nitem, 0.30, 0.95)

FC <- sim.data(nfactor=nfactor, nitem=nitem, nperson=ncperson, itf=itf,
varcov = varcov, lmu = lmu, loadings=loadings)
```

---

syntax.lavaan

*Create lavaan syntax for Thurstonian forced choice analysis*

---

### Description

This function writes a lavaan syntax given the specifications of the Thurstonian forced choice model.

### Usage

```
syntax.lavaan(blocks, itf, model, rename_list = NULL)
```

## Arguments

blocks	A matrix defining the blocks of the model. The number of rows must be the number of blocks, each row represents a block and contains the item numbers. The number of columns present the number of items per block.
itf	A vector defining the items-to-factor relation. For example 'c(1,1,1,2,2,2)' defines six items, the first three correspond to factor 1, the second three correspond to factor 2.
model	A descriptor for the model. Can be one of 'lmean', 'uc', 'irt' or 'simple2', 'simple3' or 'simple5'. The Number behind the 'simple' statement defines the Thurstone case.
rename_list	A list with two vectors to rename the objects in the syntax. Vector one is the original names, vector two the new names. Defaults to 'NULL'.

## Details

The syntax currently is able to perform model analysis for the latent utility models ('simple' and 'lmean'; Maydeu-Olivares & Böckenholt, 2005) the unconstrained factor model ('uc'; Maydeu-Olivares & Böckenholt, 2005) and the IRT model('irt'; Maydeu-Olivares & Brown, 2010). Additionally, all model types can be performed with all types of forced choice designs (full, block, partially linked block, linked block). For an overview and review see Jansen and Schulze (2023a,2023b).

The standard naming procedure  $ixiy$ , for the comparison of items  $x$  and  $y$ , can be changed by specifying the 'rename\_list' argument. The first vector of the should be the vector of original names, for example 'c('i1i2','i1i3','i2i3','Trait1','Trait2','Trait3')' the second vector should contain the new names, for example 'c('A01E12','A01C13','E01C23','Agree','Extra','Consc')'.

## Value

Returns a description of the user-specified model. Typically, the model is described using the lavaan model syntax. See 'lavaan::model.syntax' for more information.

## References

- Maydeu-Olivares, A., & Böckenholt, U. (2005). Structural equation modeling of paired-comparison and ranking data. *Psychological Methods*, 10(3), 285-304. doi:10.1037/1082989X.10.3.285
- Maydeu-Olivares, A., & Brown, A. (2010). Item response modeling of paired comparison and ranking data. *Multivariate Behavioural Research*, 45(6), 935-974. doi:10.1080/00273171.2010.531231
- Jansen, M. T., & Schulze, R. (2023a). *Linear factor analytic Thurstonian forced-choice models: Current status and issues*. Educational and Psychological Measurement.
- Jansen, M. T., & Schulze, R. (2023b, in review). *The Thurstonian linked block design: Improving Thurstonian modeling for paired comparison and ranking data*.

## Examples

```
# read data set FC
data(FC)
```

```
# set seed and define blocks
set.seed(1)
blocks <- matrix(sample(1:15,15), ncol = 3)

# define the item-to-factor relation
itf <- rep(1:3,5)

# Create lavaan model syntax
syntax.lavaan(blocks,itf,'irt')
```

---

syntax.mplus

---

*Create Mplus syntax for Thurstonian forced choice designs.*


---

## Description

This function writes and saves the Mplus syntax given the specifications of a Thurstonian forced choice design.

## Usage

```
syntax.mplus(blocks, itf, model, input_path, data_path = "myDataFile.dat",
  fscore_path = "myFactorScores.dat", title = "myFC_model", ID = FALSE,
  byblock = TRUE, estimator = "ULSMV", data_full = FALSE,
  standardized = TRUE, rename_list = NULL)
```

## Arguments

blocks	A matrix defining the blocks of the model. The number of rows must be the number of blocks, each row represents a block and contains the item numbers. The number of columns present the number of items per block.
itf	A vector defining the items-to-factor relation. For example 'c(1,1,1,2,2,2)' defines six items, the first three correspond to factor 1, the second three correspond to factor 2.
model	A descriptor for the model. Can be one of 'lmean', 'uc', 'irt' or 'simple2', 'simple3' or 'simple5'. The Number behind the 'simple' statement defines the Thurstone case.
input_path	Path to save the Mplus input file. Defaults to 'myFC_model.inp'.
data_path	Path of the data file for Mplus. Defaults to 'myDataFile.dat'.
fscore_path	Path to save the file of factor scores. Defaults to 'myFactorScores.dat'.
title	Title of the Mplus model. Defaults to 'myFC_model'.
ID	Logical. Should a ID variable be included? The ID must be the first variable in the data set. Defaults to 'FALSE'.
byblock	Logical. Should the order in Mplus variable statement be the same as in the blocks. Defaults to 'TRUE'.

estimator	Which estimator should be used? All Estimators that are available in Mplus can be used. Defaults to ‘‘ULSMV’’.
data_full	Logical. Are the data considered to be from a full design? Defaults to ‘FALSE’.
standardized	Logical. Should standardized values be computed? Defaults to ‘TRUE’.
rename_list	A list with two vectors to rename the objects in the syntax. Vector one is the original names, vector two the new names. Defaults to ‘NULL’.

### Details

The syntax currently is able to perform model analysis for the latent utility models (‘simple’ and ‘lmean’; Maydeu-Olivares & Böckenholt, 2005) the unconstrained factor model (‘uc’; Maydeu-Olivares & Böckenholt, 2005) and the IRT model(‘irt’; Maydeu-Olivares & Brown, 2010). Additionally, all model types can be performed with all types of forced choice designs (full, block, partially linked block, linked block). For an overview and review see Jansen and Schulze (2023a,2023b).

The function writes and saves the Mplus input files.

The standard naming procedure `ixiy`, for the comparison of items `x` and `y`, can be changed by specifying the ‘rename\_list’ argument. The first vector of the should be the vector of original names, for example ‘c(‘i1i2’,‘i1i3’,‘i2i3’,‘Trait1’,‘Trait2’,‘Trait3’)’ the second vector should contain the new names, for example ‘c(‘A01E12’,‘A01C13’,‘E01C23’,‘Agree’,‘Extra’,‘Consc’)’.

### Outputs —

### Value

Returns a description of the user-specified model. Typically, the model is described using the lavaan model syntax. See ‘lavaan::model.syntax’ for more information.

Saves a list Mplus input file at ‘input\_path’.

### References

Maydeu-Olivares, A., & Böckenholt, U. (2005). Structural equation modeling of paired-comparison and ranking data. *Psychological Methods*, *10*(3), 285-304. doi:10.1037/1082989X.10.3.285

Maydeu-Olivares, A., & Brown, A. (2010). Item response modeling of paired comparison and ranking data. *Multivariate Behavioural Research*, *45*(6), 935-974. doi:10.1080/00273171.2010.531231

Jansen, M. T., & Schulze, R. (2023a). *Linear factor analytic Thurstonian forced-choice models: Current status and issues*. Educational and Psychological Measurement.

Jansen, M. T., & Schulze, R. (2023b, in review). *The Thurstonian linked block design: Improving Thurstonian modeling for paired comparison and ranking data*.

### Examples

```
# read and save data set FC
data(FC)
write.table(FC,paste0(tempdir(),'/','my_data.dat'),quote=FALSE, sep=" ",
col.names = FALSE, row.names = FALSE)

# set seed and define blocks
```

```
set.seed(1)
blocks <- matrix(sample(1:15,15), ncol = 3)

# define the item-to-factor relation
itf <- rep(1:3,5)

# Create and save Mplus syntax
syntax.mplus(blocks,itf,'lmean',data_path = 'my_data.dat', data_full = TRUE,
input_path = paste0(tempdir(),'/','myFC_model'))
```

# Index

## \* datasets

- FC, [6](#)
- FC12, [6](#)
- FC\_raw, [7](#)
- FC\_scores, [7](#)

blocksort, [2](#)

count.combn, [3](#)  
count.xblocks, [4](#)

designA, [5](#)

FC, [6](#)  
FC12, [6](#)  
FC\_raw, [7](#)  
FC\_scores, [7](#)  
fit.correct, [8](#)  
fit.lavaan, [9](#)  
fit.mplus, [11](#)

get.scores, [13](#)  
get.xblocks, [15](#)  
get.xblocks.any, [16](#)

i.name, [17](#)

metablock, [18](#)  
mod.matrices, [19](#)

pair.combn, [20](#)

rankA, [20](#)  
read.mplus, [21](#)  
recode, [22](#)  
redundancies, [24](#)  
reliabiltyFS, [25](#)

sim.data, [26](#)  
syntax.lavaan, [27](#)  
syntax.mplus, [29](#)