

Package ‘mapSpain’

January 23, 2024

Type Package

Title Administrative Boundaries of Spain

Version 0.9.0

Description Administrative Boundaries of Spain at several levels
(Autonomous Communities, Provinces, Municipalities) based on the
'GISCO' 'Eurostat' database <<https://ec.europa.eu/eurostat/web/gisco>>
and 'CartoBase SIANE' from 'Instituto Geografico Nacional'
<<https://www.ign.es/>>. It also provides a 'leaflet' plugin and the
ability of downloading and processing static tiles.

License GPL-3

URL <https://ropenspain.github.io/mapSpain/>,
<https://github.com/rOpenSpain/mapSpain>

BugReports <https://github.com/rOpenSpain/mapSpain/issues>

Depends R (>= 3.6.0)

Imports countrycode (>= 1.2.0), giscoR (>= 0.2.4), rappidirs (>= 0.3.0), sf (>= 0.9.0), utils

Suggests ggplot2 (>= 3.0.0), knitr, leaflet (>= 2.0.0), png (>= 0.1-5), rmarkdown, slippymath (>= 0.3.1), terra (>= 1.1-4), testthat (>= 3.0.0), tidyterra

VignetteBuilder knitr

Config/Needs/coverage covr

Config/Needs/website ragg, reactable, rnaturalearth, tidyverse,
ropenspain/rostemplate, ropensci/rnaturalearthhires, devtools

Config/testthat.edition 3

Config/testthat.parallel true

Copyright © EuroGeographics for the administrative boundaries. Atlas
Nacional de España (ANE) CC BY 4.0 <<http://www.ign.es>>. INE
<<https://www.ine.es/en/index.htm>>

Encoding UTF-8

LazyData true

RoxigenNote 7.3.1

X-schema.org-applicationCategory cartography

X-schema.org-isPartOf <https://ropenspain.es/>

X-schema.org-keywords rOpenSpain, tiles, r, maps, spatial, rstats, r-package, municipalities, Spain, gisco, provinces, ign, administrative-boundaries, ccaa, static-tiles

NeedsCompilation no

Author Diego Hernangómez [aut, cre, cph]

(<https://orcid.org/0000-0001-8457-4658>, rOpenSpain)

Maintainer Diego Hernangómez <diego.hernangomezherrero@gmail.com>

Repository CRAN

Date/Publication 2024-01-23 20:50:02 UTC

R topics documented:

addProviderEspTiles	3
esp_check_access	4
esp_clear_cache	5
esp_codelist	6
esp_detect_cache_dir	8
esp_dict_region_code	8
esp_getTiles	10
esp_get_can_box	13
esp_get_capimun	16
esp_get_ccaa	19
esp_get_comarca	22
esp_get_country	25
esp_get_gridmap	27
esp_get_grid_BDN	29
esp_get_grid_EEA	30
esp_get_grid_ESDAC	32
esp_get_grid_MTN	34
esp_get_hydrobasin	36
esp_get_hypsobath	38
esp_get_munic	41
esp_get_nuts	44
esp_get_prov	47
esp_get_railway	50
esp_get_rivers	52
esp_get_roads	55
esp_get_simpl_prov	57
esp_make_provider	59
esp_move_can	60
esp_munic.sf	61
esp_nuts.sf	63

<i>addProviderEspTiles</i>	3
----------------------------	---

<i>esp_set_cache_dir</i>	65
<i>esp_tiles_providers</i>	66
<i>pobmun19</i>	70

Index	71
--------------	-----------

addProviderEspTiles	<i>Include base tiles of Spanish public administrations on a R href="https://CRAN.R-project.org/package=leaflet" leaflet map</i>
----------------------------	--

Description

Include tiles of public Spanish organisms to a `leaflet::leaflet()` map.

Usage

```
addProviderEspTiles(  
  map,  
  provider,  
  layerId = NULL,  
  group = NULL,  
  options = providerEspTileOptions()  
)  
  
providerEspTileOptions(...)
```

Arguments

<code>map</code>	A map widget created from <code>leaflet::leaflet()</code> .
<code>provider</code>	Name of the provider, see <code>esp_tiles_providers</code> for values available.
<code>layerId</code>	the layer id
<code>group</code>	The name of the group the newly created layers should belong to Human-friendly group names are permitted—they need not be short, identifier-style names. Any number of layers and even different types of layers (e.g. markers and polygons) can share the same group name. See <code>leaflet::addTiles()</code> .
<code>options</code>	a list of extra options for tile layers, popups, paths (circles, rectangles, polygons, ...), or other map elements
<code>...</code>	Arguments passed on to <code>leaflet::providerTileOptions()</code> .

Details

`providerEspTileOptions()` is a wrapper of `leaflet::providerTileOptions()`.

Value

A modified `leaflet::leaflet()` map object.

Source

<https://dieghernan.github.io/leaflet-providersESP/> leaflet plugin, **v1.3.3.**

See Also

`leaflet::leaflet(), leaflet::addTiles()`

`leaflet::providerTileOptions(), leaflet::tileOptions()`

Other imagery utilities: `esp_getTiles()`, `esp_make_provider()`, `esp_tiles_providers`

Examples

```
library(leaflet)
PuertadelSol <-
  leaflet() %>%
  setView(
    lat = 40.4166,
    lng = -3.7038400,
    zoom = 18
  ) %>%
  addProviderEspTiles(provider = "IGNBase.Gris") %>%
  addProviderEspTiles(provider = "RedTransporte.Carreteras")

PuertadelSol
```

`esp_check_access` *Check access to SIANE data*

Description

Check if R has access to resources at <https://github.com/rOpenSpain/mapSpain/tree/sianedata>.

Usage

`esp_check_access()`

Value

a logical.

See Also

`giscoR::gisco_check_access()`

Other helper: `esp_move_can()`

Examples

```
esp_check_access()
```

esp_clear_cache	<i>Clear your R href="https://CRAN.R-project.org/package=mapSpain" mapSpain cache dir</i>
-----------------	---

Description

Use this function with caution. This function would clear your cached data and configuration, specifically:

- Deletes the **mapSpain** config directory (`rappdirs::user_config_dir("mapSpain", "R")`).
- Deletes the `cache_dir` directory.
- Deletes the values stored on `Sys.getenv("MAPSPAIN_CACHE_DIR")` and `options(mapSpain_cache_dir)`.

Usage

```
esp_clear_cache(config = FALSE, cached_data = TRUE, verbose = FALSE)
```

Arguments

config	if TRUE, will delete the configuration folder of mapSpain .
cached_data	If this is set to TRUE, it will delete your <code>cache_dir</code> and all its content.
verbose	Logical, displays information. Useful for debugging, default is FALSE.

Details

This is an overkill function that is intended to reset your status as if you would never have installed and/or used **mapSpain**.

Value

Invisible. This function is called for its side effects.

See Also

Other cache utilities: `esp_detect_cache_dir()`, `esp_set_cache_dir()`

Examples

```
# Don't run this! It would modify your current state
## Not run:
esp_clear_cache(verbose = TRUE)

## End(Not run)

Sys.getenv("MAPSPAIN_CACHE_DIR")
```

esp_codelist	<i>Spanish Code Translation Data Frame</i>
---------------------	--

Description

A data frame used internally for translating codes and names of the different subdivisions of Spain. The data frame provides the hierarchy of the subdivisions including NUTS1 level, Autonomous Communities (equivalent to NUTS2), Provinces and NUTS3 level. See **Note**.

Format

A data frame with 59 rows codes and columns:

nuts1.code NUTS 1 code
nuts1.name NUTS 1 name
nuts1.name.alt NUTS 1 alternative name
nuts1.shortname.es NUTS1 1 short (common) name (Spanish)
codauto INE code of the autonomous community
iso2.ccaa.code ISO2 code of the autonomous community
nuts2.code NUTS 2 Code
ine.ccaa.name INE name of the autonomous community
iso2.ccaa.name.es ISO2 name of the autonomous community (Spanish)
iso2.ccaa.name.ca ISO2 name of the autonomous community (Catalan)
iso2.ccaa.name.gl ISO2 name of the autonomous community (Galician)
iso2.ccaa.name.eu ISO2 name of the autonomous community (Basque)
nuts2.name NUTS 2 name
cldr.ccaa.name.en CLDR name of the autonomous community (English)
cldr.ccaa.name.es CLDR name of the autonomous community (Spanish)
cldr.ccaa.name.ca CLDR name of the autonomous community (Catalan)
cldr.ccaa.name.ga CLDR name of the autonomous community (Galician)
cldr.ccaa.name.eu CLDR name of the autonomous community (Basque)
ccaa.shortname.en Short (common) name of the autonomous community (English)
ccaa.shortname.es Short (common) name of the autonomous community (Spanish)
ccaa.shortname.ca Short (common) name of the autonomous community (Catalan)
ccaa.shortname.ga Short (common) name of the autonomous community (Galician)
ccaa.shortname.eu Short (common) name of the autonomous community (Basque)
cpro INE code of the province
iso2.prov.code ISO2 code of the province
nuts.prov.code NUTS code of the province

ine.prov.name INE name of the province
iso2.prov.name.es ISO2 name of the province (Spanish)
iso2.prov.name.ca ISO2 name of the province (Catalan)
iso2.prov.name.ga ISO2 name of the province (Galician)
iso2.prov.name.eu ISO2 name of the province (Basque)
cldr.prov.name.en CLDR name of the province (English)
cldr.prov.name.es CLDR name of the province (Spanish)
cldr.prov.name.ca CLDR name of the province (Catalan)
cldr.prov.name.ga CLDR name of the province (Galician)
cldr.prov.name.eu CLDR name of the province (Basque)
prov.shortname.en Short (common) name of the province (English)
prov.shortname.es Short (common) name of the province (Spanish)
prov.shortname.ca Short (common) name of the province (Catalan)
prov.shortname.ga Short (common) name of the province (Galician)
prov.shortname.eu Short (common) name of the province (Basque)
nuts3.code NUTS 3 code
nuts3.name NUTS 3 name
nuts3.shortname.es NUTS 3 short (common) name

Note

Although NUTS2 matches the first subdivision level of Spain (CCAA - Autonomous Communities), it should be noted that NUTS3 does not match the second subdivision level of Spain (Provinces). NUTS3 provides a dedicated code for major islands whereas the Provinces doesn't.

Ceuta and Melilla has an specific status (Autonomous Cities) but are considered as communities with a single province (as Madrid, Asturias or Murcia) on this dataset.

Source

- INE: Instituto Nacional de Estadística: <https://www.ine.es/>
- Eurostat (NUTS): <https://ec.europa.eu/eurostat/web/nuts/overview>
- ISO: <https://www.iso.org/home.html>
- CLDR: <https://unicode-org.github.io/cldr-staging/charts/38/index.html>

See Also

Other datasets: [esp_munic.sf](#), [esp_nuts.sf](#), [esp_tiles_providers](#), [pobmun19](#)

Other political: [esp_get_can_box\(\)](#), [esp_get_capimun\(\)](#), [esp_get_ccaa\(\)](#), [esp_get_comarca\(\)](#), [esp_get_country\(\)](#), [esp_get_gridmap](#), [esp_get_munic\(\)](#), [esp_get_nuts\(\)](#), [esp_get_prov\(\)](#), [esp_get_simpl_prov\(\)](#)

Other dictionary: [esp_dict_region_code\(\)](#)

Examples

```
data("esp_codelist")
```

<code>esp_detect_cache_dir</code>	<i>Detect cache dir for project.org/package=mapSpain</i>	R href="https://CRAN.R-project.org/package=mapSpain"
-----------------------------------	--	--

Description

Helper function to detect the current cache folder. See [esp_set_cache_dir\(\)](#)

Usage

```
esp_detect_cache_dir(x = NULL)
```

Arguments

<code>x</code>	Ignored
----------------	---------

Value

A character with the path to your `cache_dir`.

See Also

Other cache utilities: [esp_clear_cache\(\)](#), [esp_set_cache_dir\(\)](#)

Examples

```
esp_detect_cache_dir()
```

<code>esp_dict_region_code</code>	<i>Convert and translate Subdivision Names</i>
-----------------------------------	--

Description

Converts long subdivision names into different coding schemes and languages.

Usage

```
esp_dict_region_code(sourcevar, origin = "text", destination = "text")
esp_dict_translate(sourcevar, lang = "en", all = FALSE)
```

Arguments

sourcevar	Vector which contains the subdivision names to be converted.
origin, destination	One of "text", "nuts", "iso2", "codauto" and "cpro".
lang	Language of translation. Available languages are: <ul style="list-style-type: none"> • "es": Spanish • "en": English • "ca": Catalan • "ga": Galician • "eu": Basque
all	Logical. Should the function return all names or not? On FALSE it returns a character vector. See Value .

Details

If no match is found for any value, the function displays a warning and returns NA for those values. Note that mixing names of different administrative levels (e.g. "Catalonia" and "Barcelona") may return empty values, depending on the destination values.

Value

`esp_dict_region_code()` returns a vector of characters.

`esp_dict_translate()` returns a character vector or a named list with each of the possible names of each sourcevar on the required language lang.

See Also

Other dictionary: `esp_codelist`

Other dictionary: `esp_codelist`

Examples

```

vals <- c("Errioxa", "Coruna", "Gerona", "Madrid")

esp_dict_region_code(vals)
esp_dict_region_code(vals, destination = "nuts")
esp_dict_region_code(vals, destination = "cpro")
esp_dict_region_code(vals, destination = "iso2")

# From ISO2 to another codes

iso2vals <- c("ES-M", "ES-S", "ES-SG")
esp_dict_region_code(iso2vals, origin = "iso2")
esp_dict_region_code(iso2vals,
  origin = "iso2",
  destination = "nuts"
)
esp_dict_region_code(iso2vals,
```

```

origin = "iso2",
destination = "cpro"
)

# Mixing levels
valsmix <- c("Centro", "Andalucia", "Seville", "Menorca")
esp_dict_region_code(valsmix, destination = "nuts")
## Not run:

# Warning

esp_dict_region_code(valsmix, destination = "codauto")
esp_dict_region_code(valsmix, destination = "iso2")

## End(Not run)

vals <- c("La Rioja", "Sevilla", "Madrid", "Jaen", "Orense", "Baleares")

esp_dict_translate(vals)
esp_dict_translate(vals, lang = "es")
esp_dict_translate(vals, lang = "ca")
esp_dict_translate(vals, lang = "eu")
esp_dict_translate(vals, lang = "ga")

esp_dict_translate(vals, lang = "ga", all = TRUE)

```

esp_getTiles*Get static tiles from public administrations of Spanish.***Description**

Get static map tiles based on a spatial object. Maps can be fetched from various open map servers.
 This function is a implementation of the javascript plugin [leaflet-providersESP v1.3.3](#).

Usage

```

esp_getTiles(
  x,
  type = "IDERioja",
  zoom = NULL,
  zoommin = 0,
  crop = TRUE,
  res = 512,
  bbox_expand = 0.05,
  transparent = TRUE,
  mask = FALSE,
  update_cache = FALSE,
  cache_dir = NULL,

```

```

    verbose = FALSE,
    options = NULL
)

```

Arguments

x	An sf or sfc object.
type	This parameter could be either: <ul style="list-style-type: none"> The name of one of the pre-defined providers (see esp_tiles_providers()). A list with two named elements id and q with your own parameters. See esp_make_provider() and examples.
zoom	Zoom level. If NULL, it is determined automatically. If set, it overrides zoommin. Only valid for WMTS tiles. On a single point it applies a buffer to the point and on zoom = NULL the function set a zoom level of 18. See Details .
zoommin	Delta on default zoom. The default value is designed to download fewer tiles than you probably want. Use 1 or 2 to increase the resolution.
crop	TRUE if results should be cropped to the specified x extent, FALSE otherwise. If x is an sf object with one POINT, crop is set to FALSE.
res	Resolution (in pixels) of the final tile. Only valid for WMS.
bbox_expand	A numeric value that indicates the expansion percentage of the bounding box of x.
transparent	Logical. Provides transparent background, if supported. Depends on the selected provider on type.
mask	TRUE if the result should be masked to x.
update_cache	A logical whether to update cache. Default is FALSE. When set to TRUE it would force a fresh download of the source file.
cache_dir	A path to a cache directory. See About caching .
verbose	Logical, displays information. Useful for debugging, default is FALSE.
options	A named list containing additional options to pass to the query.

Details

Zoom levels are described on the [OpenStreetMap wiki](#):

zoom	area to represent
0	whole world
3	large country
5	state
8	county
10	metropolitan area
11	city
13	village or suburb
16	streets
18	some buildings, trees

For a complete list of providers see [esp_tiles_providers](#).

Most WMS/WMTS providers provide tiles on "EPSG:3857". In case that the tile looks deformed, try projecting first x:

```
x <- sf::st_transform(x, 3857)
```

Value

A SpatRaster is returned, with 3 (RGB) or 4 (RGBA) layers, depending on the provider. See [terra::rast\(\)](#)..

About caching

You can set your cache_dir with [esp_set_cache_dir\(\)](#).

Sometimes cached files may be corrupt. On that case, try re-downloading the data setting update_cache = TRUE.

If you experience any problem on download, try to download the corresponding .geojson file by any other method and save it on your cache_dir. Use the option verbose = TRUE for debugging the API query.

Source

<https://dieghernan.github.io/leaflet-providersESP/> leaflet plugin, **v1.3.3**.

See Also

[terra::rast\(\)](#).

Other imagery utilities: [addProviderEspTiles\(\)](#), [esp_make_provider\(\)](#), [esp_tiles_providers](#)

Examples

```
## Not run:
# This script downloads tiles to your local machine
# Run only if you are online

segovia <- esp_get_prov_siane("segovia", epsg = 3857)
tile <- esp_getTiles(segovia, "IGNBase.Todo")

library(ggplot2)
library(tidyterra)

ggplot(segovia) +
  geom_spatraster_rgb(data = tile, maxcell = Inf) +
  geom_sf(fill = NA)

# Another provider

tile2 <- esp_getTiles(segovia, type = "MDT")

ggplot(segovia) +
  geom_spatraster_rgb(data = tile2, maxcell = Inf) +
```

```

geom_sf(fill = NA)

# A custom WMS provided

custom_wms <- esp_make_provider(
  id = "an_id_for_caching",
  q = "https://idecyl.jcyl.es/geoserver/ge/wms?",
  service = "WMS",
  version = "1.3.0",
  format = "image/png",
  layers = "geolog_cyl_litologia"
)

custom_wms_tile <- esp_getTiles(segovia, custom_wms)

autoplot(custom_wms_tile, maxcell = Inf) +
  geom_sf(data = segovia, fill = NA, color = "red")

# A custom WMTS provider

custom_wmts <- esp_make_provider(
  id = "cyl_wmts",
  q = "https://www.ign.es/wmts/pnoa-ma?",
  service = "WMTS",
  layer = "OI.OrthoimageCoverage"
)

custom_wmts_tile <- esp_getTiles(segovia, custom_wmts)

autoplot(custom_wmts_tile, maxcell = Inf) +
  geom_sf(data = segovia, fill = NA, color = "white", linewidth = 2)

# Example from https://leaflet-extras.github.io/leaflet-providers/preview/
cartodb_voyager <- list(
  id = "CartoDB_Voyager",
  q = "https://a.basemaps.cartocdn.com/rastertiles/voyager/{z}/{x}/{y}.png"
)
cartodb <- esp_getTiles(segovia, cartodb_voyager, zoommin = 1)

autoplot(cartodb, maxcell = Inf) +
  geom_sf(data = segovia, fill = NA, color = "black", linewidth = 1)

## End(Not run)

```

Description

When plotting Spain, it is usual to represent the Canary Islands as an inset (see `moveCAN` on [esp_get_nuts\(\)](#)). These functions provides complementary lines and polygons to be used when the Canary Islands are displayed as an inset.

- `esp_get_can_box()` is used to draw lines around the displaced Canary Islands.
- `esp_get_can_provinces()` is used to draw a separator line between the two provinces of the Canary Islands.

See also [esp_move_can\(\)](#) to displace stand-alone objects on the Canary Islands.

Usage

```
esp_get_can_box(style = "right", moveCAN = TRUE, epsg = "4258")

esp_get_can_provinces(moveCAN = TRUE, epsg = "4258")
```

Arguments

<code>style</code>	Style of line around Canary Islands. Four options available: "left", "right", "box" or "poly".
<code>moveCAN</code>	A logical TRUE/FALSE or a vector of coordinates <code>c(lat, lon)</code> . It places the Canary Islands close to Spain's mainland. Initial position can be adjusted using the vector of coordinates. See Displacing the Canary Islands .
<code>epsg</code>	projection of the map: 4-digit EPSG code . One of: <ul style="list-style-type: none"> • "4258": ETRS89 • "4326": WGS84 • "3035": ETRS89 / ETRS-LAEA • "3857": Pseudo-Mercator

Value

A `sf` polygon or line depending of `style` parameter.

`esp_get_can_provinces` returns a `LINESTRING` object.

Displacing the Canary Islands

While `moveCAN` is useful for visualization, it would alter the actual geographic position of the Canary Islands. When using the output for spatial analysis or using tiles (e.g. with `esp_getTiles()` or `addProviderEspTiles()`) this option should be set to FALSE in order to get the actual coordinates, instead of the modified ones. See also [esp_move_can\(\)](#) for displacing stand-alone `sf` objects.

Source

`esp_get_can_provinces` extracted from CartoBase ANE, se89_mult_admin_provcan_1.shp file.

See Also

Other political: [esp_codelist](#), [esp_get_capimun\(\)](#), [esp_get_ccaa\(\)](#), [esp_get_comarca\(\)](#), [esp_get_country\(\)](#), [esp_get_gridmap](#), [esp_get_munic\(\)](#), [esp_get_nuts\(\)](#), [esp_get_prov\(\)](#), [esp_get_simpl_prov\(\)](#)

Other Canary Islands: [esp_move_can\(\)](#)

Examples

```
Provs <- esp_get_prov()
Box <- esp_get_can_box()
Line <- esp_get_can_provinces()

# Plot
library(ggplot2)

ggplot(Provs) +
  geom_sf() +
  geom_sf(data = Box) +
  geom_sf(data = Line) +
  theme_linedraw()

# Displacing Canary

# By same factor

displace <- c(15, 0)

Provs_D <- esp_get_prov(moveCAN = displace)

Box_D <- esp_get_can_box(style = "left", moveCAN = displace)

Line_D <- esp_get_can_provinces(moveCAN = displace)

ggplot(Provs_D) +
  geom_sf() +
  geom_sf(data = Box_D) +
  geom_sf(data = Line_D) +
  theme_linedraw()

# Example with poly option

# Get countries with giscoR

library(giscoR)

# Low resolution map
res <- "20"

Countries <-
  gisco_get_countries(
    res = res,
```

```

epsg = "4326",
country = c("France", "Portugal", "Andorra", "Morocco", "Argelia")
)
CANbox <-
  esp_get_can_box(
    style = "poly",
    epsg = "4326",
    moveCAN = c(12.5, 0)
  )

CCAA <- esp_get_ccaa(
  res = res,
  epsg = "4326",
  moveCAN = c(12.5, 0) # Same displacement factor
)

# Plot

ggplot(Countries) +
  geom_sf(fill = "#DFDFDF") +
  geom_sf(data = CANbox, fill = "#C7E7FB", linewidth = 1) +
  geom_sf(data = CCAA, fill = "#FDFBEA") +
  coord_sf(
    xlim = c(-10, 4.3),
    ylim = c(34.6, 44)
  ) +
  theme(
    panel.background = element_rect(fill = "#C7E7FB"),
    panel.grid = element_blank()
  )

```

esp_get_capimun

Get R href="https://CRAN.R-project.org/package=sfsf points of the municipalities of Spain

Description

Get a **sf** point with the location of the political powers for each municipality (possibly the center of the municipality).

Note that this differs of the centroid of the boundaries of the municipality, returned by [esp_get_munic\(\)](#).

Usage

```

esp_get_capimun(
  year = Sys.Date(),
  epsg = "4258",
  cache = TRUE,
  update_cache = FALSE,

```

```

    cache_dir = NULL,
    verbose = FALSE,
    region = NULL,
    munic = NULL,
    moveCAN = TRUE,
    rawcols = FALSE
)

```

Arguments

year	Release year. See Details for years available.
epsg	projection of the map: 4-digit EPSG code . One of: <ul style="list-style-type: none"> • "4258": ETRS89 • "4326": WGS84 • "3035": ETRS89 / ETRS-LAEA • "3857": Pseudo-Mercator
cache	A logical whether to do caching. Default is TRUE. See About caching .
update_cache	A logical whether to update cache. Default is FALSE. When set to TRUE it would force a fresh download of the source file.
cache_dir	A path to a cache directory. See About caching .
verbose	Logical, displays information. Useful for debugging, default is FALSE.
region	A vector of names and/or codes for provinces or NULL to get all the municipalities. See Details .
munic	A name or regex expression with the names of the required municipalities. NULL would not produce any filtering.
moveCAN	A logical TRUE/FALSE or a vector of coordinates c(lat, lon). It places the Canary Islands close to Spain's mainland. Initial position can be adjusted using the vector of coordinates. See Displacing the Canary Islands .
rawcols	Logical. Setting this to TRUE would add the raw columns of the dataset provided by IGN.

Details

year could be passed as a single year (YYYY format, as end of year) or as a specific date (YYYY-MM-DD format). Historical information starts as of 2005.

When using region you can use and mix names and NUTS codes (levels 1, 2 or 3), ISO codes (corresponding to level 2 or 3) or cpro. See [esp_codelist](#)

When calling a superior level (Province, Autonomous Community or NUTS1), all the municipalities of that level would be added.

Value

A **sf** point object.

About caching

You can set your `cache_dir` with `esp_set_cache_dir()`.

Sometimes cached files may be corrupt. On that case, try re-downloading the data setting `update_cache = TRUE`.

If you experience any problem on download, try to download the corresponding `.geojson` file by any other method and save it on your `cache_dir`. Use the option `verbose = TRUE` for debugging the API query.

Displacing the Canary Islands

While `moveCAN` is useful for visualization, it would alter the actual geographic position of the Canary Islands. When using the output for spatial analysis or using tiles (e.g. with `esp_getTiles()` or `addProviderEspTiles()`) this option should be set to `FALSE` in order to get the actual coordinates, instead of the modified ones. See also `esp_move_can()` for displacing stand-alone `sf` objects.

Source

IGN data via a custom CDN (see <https://github.com/rOpenSpain/mapSpain/tree/sianedata>).

See Also

Other political: `esp_codelist`, `esp_get_can_box()`, `esp_get_ccaa()`, `esp_get_comarca()`, `esp_get_country()`, `esp_get_gridmap`, `esp_get_munic()`, `esp_get_nuts()`, `esp_get_prov()`, `esp_get_simpl_prov()`

Other municipalities: `esp_get_munic()`, `esp_munic.sf`

Examples

```
## Not run:
# This code compares centroids of municipalities against esp_get_capimun
# It also download tiles, make sure you are online

library(sf)

# Get shape
area <- esp_get_munic_siane(munic = "Valladolid", epsg = 3857)

# Area in km2
print(paste0(round(as.double(sf::st_area(area)) / 1000000, 2), " km2"))

# Extract centroid
centroid <- sf::st_centroid(area)
centroid$type <- "Centroid"

# Compare with capimun
capimun <- esp_get_capimun(munic = "Valladolid", epsg = 3857)
capimun$type <- "Capimun"

# Get a tile to check
tile <- esp_getTiles(area, "IGNBase.Todo", zoommin = 2)
```

```

# Join both point geometries
points <- rbind(
  centroid[, "type"],
  capimun[, "type"]
)

# Check on plot
library(ggplot2)
library(tidyterra)

ggplot(points) +
  geom_spatraster_rgb(data = tile, maxcell = Inf) +
  geom_sf(data = area, fill = NA, color = "blue") +
  geom_sf(data = points, aes(fill = type), size = 5, shape = 21) +
  scale_fill_manual(values = c("green", "red")) +
  theme_void() +
  labs(title = "Centroid vs. capimun")

## End(Not run)

```

esp_get_ccaa*Get Autonomous Communities of Spain as R href="https://CRAN.R-project.org/package=sfsf" polygons and points*

Description

Returns Autonomous Communities of Spain as polygons and points at a specified scale.

- `esp_get_ccaa()` uses GISCO (Eurostat) as source. Please use [giscoR::gisco_attributions\(\)](#)
- `esp_get_ccaa_siane()` uses CartoBase ANE as source, provided by Instituto Geografico Nacional (IGN), <http://www.ign.es/web/ign/portal>. Years available are 2005 up to today.

Usage

```

esp_get_ccaa(ccaa = NULL, moveCAN = TRUE, ...)

esp_get_ccaa_siane(
  ccaa = NULL,
  year = Sys.Date(),
  epsg = "4258",
  cache = TRUE,
  update_cache = FALSE,
  cache_dir = NULL,
  verbose = FALSE,
  resolution = "3",
  moveCAN = TRUE,
  rawcols = FALSE
)

```

Arguments

<code>ccaa</code>	A vector of names and/or codes for autonomous communities or NULL to get all the autonomous communities. See Details .
<code>moveCAN</code>	A logical TRUE/FALSE or a vector of coordinates <code>c(lat, lon)</code> . It places the Canary Islands close to Spain's mainland. Initial position can be adjusted using the vector of coordinates. See Displacing the Canary Islands .
<code>...</code>	Arguments passed on to esp_get_nuts
<code>spatialtype</code>	Type of geometry to be returned: <ul style="list-style-type: none"> • "LB": Labels - point object. • "RG": Regions - polygon object.
<code>year</code>	Release year. See esp_get_nuts() for esp_get_ccaa() and Details for esp_get_ccaa_siane()
<code>epsg</code>	projection of the map: 4-digit EPSG code . One of: <ul style="list-style-type: none"> • "4258": ETRS89 • "4326": WGS84 • "3035": ETRS89 / ETRS-LAEA • "3857": Pseudo-Mercator
<code>cache</code>	A logical whether to do caching. Default is TRUE. See About caching .
<code>update_cache</code>	A logical whether to update cache. Default is FALSE. When set to TRUE it would force a fresh download of the source file.
<code>cache_dir</code>	A path to a cache directory. See About caching .
<code>verbose</code>	Logical, displays information. Useful for debugging, default is FALSE.
<code>resolution</code>	Resolution of the polygon. Values available are 3, 6.5 or 10.
<code>rawcols</code>	Logical. Setting this to TRUE would add the raw columns of the dataset provided by IGN.

Details

When using `ccaa` you can use and mix names and NUTS codes (levels 1 or 2), ISO codes (corresponding to level 2) or codauto (see [esp_codelist](#)). Ceuta and Melilla are considered as Autonomous Communities on this function.

When calling a NUTS1 level, all the Autonomous Communities of that level would be added.

On [esp_get_ccaa_siane\(\)](#), `year` could be passed as a single year (YYYY format, as end of year) or as a specific date (YYYY-MM-DD format). Historical information starts as of 2005.

Value

A **sf** object specified by `spatialtype`.

About caching

You can set your `cache_dir` with [esp_set_cache_dir\(\)](#).

Sometimes cached files may be corrupt. On that case, try re-downloading the data setting `update_cache = TRUE`.

If you experience any problem on download, try to download the corresponding .geojson file by any other method and save it on your `cache_dir`. Use the option `verbose = TRUE` for debugging the API query.

Displacing the Canary Islands

While `moveCAN` is useful for visualization, it would alter the actual geographic position of the Canary Islands. When using the output for spatial analysis or using tiles (e.g. with `esp_getTiles()` or `addProviderEspTiles()`) this option should be set to FALSE in order to get the actual coordinates, instead of the modified ones. See also `esp_move_can()` for displacing stand-alone `sf` objects.

Source

IGN data via a custom CDN (see <https://github.com/rOpenSpain/mapSpain/tree/sianedata>).

See Also

Other political: `esp_codelist`, `esp_get_can_box()`, `esp_get_capimun()`, `esp_get_comarca()`, `esp_get_country()`, `esp_get_gridmap`, `esp_get_munic()`, `esp_get_nuts()`, `esp_get_prov()`, `esp_get_simpl_prov()`

Examples

```
ccaa <- esp_get_ccaa()

library(ggplot2)

ggplot(ccaa) +
  geom_sf()

# Random CCAA
Random <- esp_get_ccaa(ccaa = c(
  "Euskadi",
  "Catalunya",
  "ES-EX",
  "Canarias",
  "ES52",
  "01"
))

ggplot(Random) +
  geom_sf(aes(fill = codauto), show.legend = FALSE) +
  geom_sf_label(aes(label = codauto), alpha = 0.3)

# All CCAA of a Zone plus an addition

Mix <-
  esp_get_ccaa(ccaa = c("La Rioja", "Noroeste"))

ggplot(Mix) +
  geom_sf()
```

```
# Combine with giscoR to get countries

library(giscoR)
library(sf)

res <- 20 # Set same resolution

europe <- gisco_get_countries(resolution = res)
ccaa <- esp_get_ccaa(moveCAN = FALSE, resolution = res)

# Transform to same CRS
europe <- st_transform(europe, 3035)
ccaa <- st_transform(ccaa, 3035)

ggplot(europe) +
  geom_sf(fill = "#DFDFDF", color = "#656565") +
  geom_sf(data = ccaa, fill = "#FDFBEA", color = "#656565") +
  coord_sf(
    xlim = c(23, 74) * 10e4,
    ylim = c(14, 55) * 10e4
  ) +
  theme(panel.background = element_rect(fill = "#C7E7FB"))
```

`esp_get_comarca` Get 'comarcas' of Spain as R
[R](https://CRAN.R-project.org/package=sfsf) <https://CRAN.R-project.org/package=sfsf> polygons

Description

Returns 'comarcas' of Spain as polygons, as provided by the **INE** (Instituto Nacional de Estadística).

Usage

```
esp_get_comarca(
  region = NULL,
  comarca = NULL,
  moveCAN = TRUE,
  epsg = "4258",
  update_cache = FALSE,
  cache_dir = NULL,
  verbose = FALSE
)
```

Arguments

<code>region</code>	A vector of names and/or codes for provinces or <code>NULL</code> to get all the comarcas., See Details .
---------------------	---

comarca	A name or regex expression with the names of the required comarcas. NULL would not produce any filtering.
moveCAN	A logical TRUE/FALSE or a vector of coordinates c(lat, lon). It places the Canary Islands close to Spain's mainland. Initial position can be adjusted using the vector of coordinates. See Displacing the Canary Islands .
epsg	projection of the map: 4-digit EPSG code . One of: <ul style="list-style-type: none"> • "4258": ETRS89 • "4326": WGS84 • "3035": ETRS89 / ETRS-LAEA • "3857": Pseudo-Mercator
update_cache	A logical whether to update cache. Default is FALSE. When set to TRUE it would force a fresh download of the source file.
cache_dir	A path to a cache directory. See About caching .
verbose	Logical, displays information. Useful for debugging, default is FALSE.

Details

'Comarcas' (English equivalent: district, county, area or zone) does not always have a formal legal status. They correspond mainly to natural areas (valleys, river basins etc.) or even to historical regions or ancient kingdoms.

When using `region` you can use and mix names and NUTS codes (levels 1, 2 or 3), ISO codes (corresponding to level 2 or 3) or "cpro" (see [esp_codelist](#)).

When calling a superior level (Province, Autonomous Community or NUTS1), all the comarcas of that level would be added.

Legal Notice:

The use of the information contained on the [INE website](#) may be carried out by users or re-use agents, at their own risk, and they will be the sole liable parties in the case of having to answer to third parties due to damages arising from such use.

Value

A [sf](#) polygon object.

About caching

You can set your `cache_dir` with [esp_set_cache_dir\(\)](#).

Sometimes cached files may be corrupt. On that case, try re-downloading the data setting `update_cache = TRUE`.

If you experience any problem on download, try to download the corresponding .geojson file by any other method and save it on your `cache_dir`. Use the option `verbose = TRUE` for debugging the API query.

Displacing the Canary Islands

While `moveCAN` is useful for visualization, it would alter the actual geographic position of the Canary Islands. When using the output for spatial analysis or using tiles (e.g. with `esp_getTiles()` or `addProviderEspTiles()`) this option should be set to FALSE in order to get the actual coordinates, instead of the modified ones. See also `esp_move_can()` for displacing stand-alone `sf` objects.

Source

INE: PC_Axis files.

See Also

Other political: `esp_codelist`, `esp_get_can_box()`, `esp_get_capimun()`, `esp_get_ccaa()`, `esp_get_country()`, `esp_get_gridmap`, `esp_get_munic()`, `esp_get_nuts()`, `esp_get_prov()`, `esp_get_simpl_prov()`

Examples

```
comarcas <- esp_get_comarca(moveCAN = FALSE)

library(ggplot2)

ggplot(comarcas) +
  geom_sf()

# Comarcas of Castille and Leon

comarcas_cyl <- esp_get_comarca("Castilla y Leon")

ggplot(comarcas_cyl) +
  geom_sf(aes(fill = ine.prov.name)) +
  labs(fill = "Province")

# Comarcas with Mountains or Alt(o,a) in the name

comarcas_alto <- esp_get_comarca(
  comarca = "Montaña|Monte|Sierra|Alt",
  epsg = 3857
)

ggplot(comarcas_alto) +
  geom_sf(aes(fill = ine.ccaa.name)) +
  geom_sf_text(aes(label = name), check_overlap = TRUE) +
  labs(fill = "CCAA")
```

esp_get_country *Get the borders of Spain as a R href="https://CRAN.R-project.org/package=sf" sf polygon*

Description

Returns the boundaries of Spain as a single **sf** polygon at a specified scale.

Usage

```
esp_get_country(moveCAN = TRUE, ...)
```

Arguments

moveCAN	A logical TRUE/FALSE or a vector of coordinates c(lat, lon). It places the Canary Islands close to Spain's mainland. Initial position can be adjusted using the vector of coordinates. See Displacing the Canary Islands .
...	Arguments passed on to esp_get_nuts
year	Release year of the file. One of "2003", "2006", "2010", "2013", "2016" or "2021".
epsg	projection of the map: 4-digit EPSG code . One of: <ul style="list-style-type: none">• "4258": ETRS89• "4326": WGS84• "3035": ETRS89 / ETRS-LAEA• "3857": Pseudo-Mercator
cache	A logical whether to do caching. Default is TRUE. See About caching .
update_cache	A logical whether to update cache. Default is FALSE. When set to TRUE it would force a fresh download of the source file.
cache_dir	A path to a cache directory. See About caching .
verbose	Logical, displays information. Useful for debugging, default is FALSE.
resolution	Resolution of the geospatial data. One of <ul style="list-style-type: none">• "60": 1:60million• "20": 1:20million• "10": 1:10million• "03": 1:3million• "01": 1:1million

Value

A **sf** polygon object.

About caching

You can set your `cache_dir` with [esp_set_cache_dir\(\)](#).

Sometimes cached files may be corrupt. On that case, try re-downloading the data setting `update_cache = TRUE`.

If you experience any problem on download, try to download the corresponding .geojson file by any other method and save it on your `cache_dir`. Use the option `verbose = TRUE` for debugging the API query.

Displacing the Canary Islands

While `moveCAN` is useful for visualization, it would alter the actual geographic position of the Canary Islands. When using the output for spatial analysis or using tiles (e.g. with [esp_getTiles\(\)](#) or [addProviderEspTiles\(\)](#)) this option should be set to FALSE in order to get the actual coordinates, instead of the modified ones. See also [esp_move_can\(\)](#) for displacing stand-alone `sf` objects.

See Also

Other political: [esp_codelist](#), [esp_get_can_box\(\)](#), [esp_get_capimun\(\)](#), [esp_get_ccaa\(\)](#), [esp_get_comarca\(\)](#), [esp_get_gridmap](#), [esp_get_munic\(\)](#), [esp_get_nuts\(\)](#), [esp_get_prov\(\)](#), [esp_get_simpl_prov\(\)](#)

Examples

```
OriginalCan <- esp_get_country(moveCAN = FALSE)

# One row only

nrow(OriginalCan)

library(ggplot2)

ggplot(OriginalCan) +
  geom_sf(fill = "grey70")

# Less resolution

MovedCan <- esp_get_country(moveCAN = TRUE, resolution = "20")

library(ggplot2)

ggplot(MovedCan) +
  geom_sf(fill = "grey70")
```

esp_get_gridmap	<i>Get a R href="https://CRAN.R-project.org/package=sfsf" hexbin or squared polygon of Spain</i>
-----------------	--

Description

Loads a hexbin map (**sf** object) or a map of squares with the boundaries of the provinces or autonomous communities of Spain.

Usage

```
esp_get_hex_prov(prov = NULL)

esp_get_hex_ccaa(ccaa = NULL)

esp_get_grid_prov(prov = NULL)

esp_get_grid_ccaa(ccaa = NULL)
```

Arguments

prov	A vector of names and/or codes for provinces or NULL to get all the provinces. See Details .
ccaa	A vector of names and/or codes for autonomous communities or NULL to get all the autonomous communities. See Details .

Details

Hexbin or grid map has an advantage over usual choropleth maps. In choropleths, a large polygon data looks more emphasized just because of its size, what introduces a bias. Here with hexbin, each region is represented equally dismissing the bias.

You can use and mix names, ISO codes, "codauto"/"cpro" codes (see [esp_codelist](#)) and NUTS codes of different levels.

When using a code corresponding of a higher level (e.g. `esp_get_prov("Andalucia")`) all the corresponding units of that level are provided (in this case , all the provinces of Andalucia).

Results are provided in **EPSG:4258**, use [`sf::st_transform\(\)`](#) to change the projection.

Value

A **sf** POLYGON object.

See Also

Other political: [`esp_codelist`](#), [`esp_get_can_box\(\)`](#), [`esp_get_capimun\(\)`](#), [`esp_get_ccaa\(\)`](#), [`esp_get_comarca\(\)`](#), [`esp_get_country\(\)`](#), [`esp_get_munic\(\)`](#), [`esp_get_nuts\(\)`](#), [`esp_get_prov\(\)`](#), [`esp_get_simpl_prov\(\)`](#)

Examples

```

esp <- esp_get_country()
hexccaa <- esp_get_hex_ccaa()

library(ggplot2)

ggplot(hexccaa) +
  geom_sf(data = esp) +
  geom_sf(aes(fill = codauto),
          alpha = 0.3,
          show.legend = FALSE
  ) +
  geom_sf_text(aes(label = label), check_overlap = TRUE) +
  theme_void() +
  labs(title = "Hexbin: CCAA")

hexprov <- esp_get_hex_prov()

ggplot(hexprov) +
  geom_sf(data = esp) +
  geom_sf(aes(fill = codauto),
          alpha = 0.3,
          show.legend = FALSE
  ) +
  geom_sf_text(aes(label = label), check_overlap = TRUE) +
  theme_void() +
  labs(title = "Hexbin: Provinces")

gridccaa <- esp_get_grid_ccaa()

ggplot(gridccaa) +
  geom_sf(data = esp) +
  geom_sf(aes(fill = codauto),
          alpha = 0.3,
          show.legend = FALSE
  ) +
  geom_sf_text(aes(label = label), check_overlap = TRUE) +
  theme_void() +
  labs(title = "Grid: CCAA")

gridprov <- esp_get_grid_prov()

ggplot(gridprov) +
  geom_sf(data = esp) +
  geom_sf(aes(fill = codauto),

```

```

        alpha = 0.3,
        show.legend = FALSE
    ) +
    geom_sf_text(aes(label = label), check_overlap = TRUE) +
    theme_void() +
    labs(title = "Grid: Provinces")

```

esp_get_grid_BDN

Get R href="https://CRAN.R-project.org/package=sf" polygons of the national geographic grids provided by BDN

Description

Loads a **sf** polygon with the geographic grids of Spain as provided on the Banco de Datos de la Naturaleza (Nature Data Bank), by the Ministry of Environment (MITECO):

- `esp_get_grid_BDN()` extracts country-wide grids with resolutions 5x5 or 10x10 kms.
- `esp_get_grid_BDN_ccaa()` extracts grids by Autonomous Community with resolution 1x1 km.

Usage

```

esp_get_grid_BDN(
  resolution = 10,
  type = "main",
  update_cache = FALSE,
  cache_dir = NULL,
  verbose = FALSE
)

esp_get_grid_BDN_ccaa(
  ccaa,
  update_cache = FALSE,
  cache_dir = NULL,
  verbose = FALSE
)

```

Arguments

<code>resolution</code>	Resolution of the grid in kms. Could be 5 or 10.
<code>type</code>	The scope of the grid. It could be mainland Spain ("main") or the Canary Islands ("canary").
<code>update_cache</code>	A logical whether to update cache. Default is FALSE. When set to TRUE it would force a fresh download of the source file.
<code>cache_dir</code>	A path to a cache directory. See About caching .
<code>verbose</code>	Logical, displays information. Useful for debugging, default is FALSE.
<code>ccaa</code>	A vector of names and/or codes for autonomous communities. See Details on <code>esp_get_ccaa()</code> .

Value

A **sf** polygon

About caching

You can set your `cache_dir` with `esp_set_cache_dir()`.

Sometimes cached files may be corrupt. On that case, try re-downloading the data setting `update_cache = TRUE`.

If you experience any problem on download, try to download the corresponding .geojson file by any other method and save it on your `cache_dir`. Use the option `verbose = TRUE` for debugging the API query.

Source

BDN data via a custom CDN (see <https://github.com/rOpenSpain/mapSpain/tree/sianedata/MTN>).

See original metadata and source on <https://www.miteco.gob.es/es/biodiversidad/servicios/banco-datos-naturaleza/informacion-disponible/bdn-cart-aux-descargas-ccaa.html>

See Also

`esp_get_ccaa()`

Other grids: `esp_get_grid_EEA()`, `esp_get_grid_ESDAC()`, `esp_get_grid_MTN()`

Examples

```
grid <- esp_get_grid_BDN(resolution = "10", type = "main")

library(ggplot2)

ggplot(grid) +
  geom_sf() +
  theme_light() +
  labs(title = "BDN Grid for Spain")
```

`esp_get_grid_EEA`

Get R href="https://CRAN.R-project.org/package=sfsf polygons of the national geographic grids provided by EEA

Description

Loads a **sf** polygon with the geographic grids of Spain as provided by the European Environment Agency (EEA).

Usage

```
esp_get_grid_EEA(
  resolution = 100,
  type = "main",
  update_cache = FALSE,
  cache_dir = NULL,
  verbose = FALSE
)
```

Arguments

resolution	Resolution of the grid in kms. Could be 1, 10 or 100.
type	The scope of the grid. It could be mainland Spain ("main") or the Canary Islands ("canary").
update_cache	A logical whether to update cache. Default is FALSE. When set to TRUE it would force a fresh download of the source file.
cache_dir	A path to a cache directory. See About caching .
verbose	Logical, displays information. Useful for debugging, default is FALSE.

Value

A **sf** polygon

About caching

You can set your `cache_dir` with [esp_set_cache_dir\(\)](#).

Sometimes cached files may be corrupt. On that case, try re-downloading the data setting `update_cache = TRUE`.

If you experience any problem on download, try to download the corresponding .geojson file by any other method and save it on your `cache_dir`. Use the option `verbose = TRUE` for debugging the API query.

Source

[EEA reference grid](#).

See Also

Other grids: [esp_get_grid_BDN\(\)](#), [esp_get_grid_ESDAC\(\)](#), [esp_get_grid_MTN\(\)](#)

Examples

```
## Not run:

grid <- esp_get_grid_EEA(type = "main", resolution = 100)
grid_can <- esp_get_grid_EEA(type = "canary", resolution = 100)
esp <- esp_get_country(moveCAN = FALSE)
```

```
library(ggplot2)

ggplot(grid) +
  geom_sf() +
  geom_sf(data = grid_can) +
  geom_sf(data = esp, fill = NA) +
  theme_light() +
  labs(title = "EEA Grid for Spain")

## End(Not run)
```

esp_get_grid_ESDAC

Get R href="https://CRAN.R-project.org/package=sfsf" polygons of the national geographic grids provided by ESDAC

Description

Loads a **sf** polygon with the geographic grids of Spain as provided by the European Soil Data Centre (ESDAC).

Usage

```
esp_get_grid_ESDAC(
  resolution = 10,
  update_cache = FALSE,
  cache_dir = NULL,
  verbose = FALSE
)
```

Arguments

resolution	Resolution of the grid in kms. Could be 1 or 10.
update_cache	A logical whether to update cache. Default is FALSE. When set to TRUE it would force a fresh download of the source file.
cache_dir	A path to a cache directory. See About caching .
verbose	Logical, displays information. Useful for debugging, default is FALSE.

Value

A **sf** polygon

About caching

You can set your cache_dir with [esp_set_cache_dir\(\)](#).

Sometimes cached files may be corrupt. On that case, try re-downloading the data setting update_cache = TRUE.

If you experience any problem on download, try to download the corresponding .geojson file by any other method and save it on your cache_dir. Use the option verbose = TRUE for debugging the API query.

Source

[EEA reference grid](#).

References

- Panagos P., Van Liedekerke M., Jones A., Montanarella L., "European Soil Data Centre: Response to European policy support and public data requirements"; (2012) *Land Use Policy*, 29 (2), pp. 329-338. [doi:10.1016/j.landusepol.2011.07.003](https://doi.org/10.1016/j.landusepol.2011.07.003)
- European Soil Data Centre (ESDAC), esdac.jrc.ec.europa.eu, European Commission, Joint Research Centre.

See Also

Other grids: [esp_get_grid_BDN\(\)](#), [esp_get_grid_EEA\(\)](#), [esp_get_grid_MTN\(\)](#)

Examples

```
## Not run:  
grid <- esp_get_grid_ESDAC()  
esp <- esp_get_country(moveCAN = FALSE)  
  
library(ggplot2)  
  
ggplot(grid) +  
  geom_sf() +  
  geom_sf(data = esp, color = "grey50", fill = NA) +  
  theme_light() +  
  labs(title = "ESDAC Grid for Spain")  
  
## End(Not run)
```

<code>esp_get_grid_MTN</code>	<i>Get R href="https://CRAN.R-project.org/package=sfsf" polygons of the national geographic grids provided by IGN</i>
-------------------------------	---

Description

Loads a **sf** polygon with the geographic grids of Spain.

Usage

```
esp_get_grid_MTN(
  grid = "MTN25_ED50_Peninsula_Baleares",
  update_cache = FALSE,
  cache_dir = NULL,
  verbose = FALSE
)
```

Arguments

<code>grid</code>	Name of the grid to be loaded. See Details .
<code>update_cache</code>	A logical whether to update cache. Default is FALSE. When set to TRUE it would force a fresh download of the source file.
<code>cache_dir</code>	A path to a cache directory. See About caching .
<code>verbose</code>	Logical, displays information. Useful for debugging, default is FALSE.

Details

Metadata available on <https://github.com/rOpenSpain/mapSpain/tree/sianedata/MTN>.

Possible values of `grid` are:

grid_name	MTN25_ED50_Peninsula_Baleares
	MTN25_ED50_ceuta_melilla_alboran
	MTN25_ED50_Peninsula_Baleares_Canarias
	MTN25_RegCan95_Canarias
	MTN50_ED50_Peninsula_Baleares
	MTN50_ED50_ceuta_melilla_alboran
	MTN50_RegCan95_Canarias

MTN Grids:

A description of the MTN (Mapa Topografico Nacional) grids available:

MTN25_ED50_Peninsula_Baleares

MTN25 grid corresponding to the Peninsula and Balearic Islands, in ED50 and geographical coordinates (longitude, latitude) This is the real MTN25 grid, that is, the one that divides the current printed series of the map, taking into account special sheets and irregularities.

MTN50_ED50_Peninsula_Baleares

MTN50 grid corresponding to the Peninsula and Balearic Islands, in ED50 and geographical coordinates (longitude, latitude). This is the real MTN50 grid, that is, the one that divides the current printed series of the map, taking into account special sheets and irregularities.

MTN25_ETRS89_ceuta_melilla_alboran

MTN25 grid corresponding to Ceuta, Melilla, Alboran and Spanish territories in North Africa, adjusted to the new official geodetic reference system ETRS89, in geographical coordinates (longitude, latitude).

MTN25_ETRS89_Peninsula_Baleares_Canarias

MTN25 real grid corresponding to the Peninsula, the Balearic Islands and the Canary Islands, adjusted to the new ETRS89 official reference geodetic system, in geographical coordinates (longitude, latitude).

MTN50_ETRS89_Peninsula_Baleares_Canarias

MTN50 real grid corresponding to the Peninsula, the Balearic Islands and the Canary Islands, adjusted to the new ETRS89 official reference geodetic system, in geographical coordinates (longitude, latitude).

MTN25_RegCan95_Canarias

MTN25 grid corresponding to the Canary Islands, in REGCAN95 (WGS84 compatible) and geographic coordinates (longitude, latitude). It is the real MTN25 grid, that is, the one that divides the current printed series of the map, taking into account the special distribution of the Canary Islands sheets.

MTN50_RegCan95_Canarias

MTN50 grid corresponding to the Canary Islands, in REGCAN95 (WGS84 compatible) and geographic coordinates (longitude, latitude). This is the real grid of the MTN50, that is, the one that divides the current printed series of the map, taking into account the special distribution of the Canary Islands sheets.

Value

A **sf** polygon

About caching

You can set your `cache_dir` with `esp_set_cache_dir()`.

Sometimes cached files may be corrupt. On that case, try re-downloading the data setting `update_cache = TRUE`.

If you experience any problem on download, try to download the corresponding .geojson file by any other method and save it on your `cache_dir`. Use the option `verbose = TRUE` for debugging the API query.

Source

IGN data via a custom CDN (see <https://github.com/rOpenSpain/mapSpain/tree/sianedata/MTN>).

See Also

Other grids: `esp_get_grid_BDN()`, `esp_get_grid_EEA()`, `esp_get_grid_ESDAC()`

Examples

```
grid <- esp_get_grid_MTN(grid = "MTN50_ETRS89_Peninsula_Baleares_Canarias")

library(ggplot2)

ggplot(grid) +
  geom_sf() +
  theme_light() +
  labs(title = "MTN50 Grid for Spain")
```

`esp_get_hydrobasin`

Get R href="https://CRAN.R-project.org/package=sfsf" polygons of the drainage basin demarcations of Spain

Description

Loads a **sf** polygon object containing areas with the required hydrographic elements of Spain.

Usage

```
esp_get_hydrobasin(
  epsg = "4258",
  cache = TRUE,
  update_cache = FALSE,
  cache_dir = NULL,
  verbose = FALSE,
  resolution = "3",
  domain = "land"
)
```

Arguments

<code>epsg</code>	projection of the map: 4-digit EPSG code . One of:
	<ul style="list-style-type: none"> • "4258": ETRS89 • "4326": WGS84 • "3035": ETRS89 / ETRS-LAEA • "3857": Pseudo-Mercator
<code>cache</code>	A logical whether to do caching. Default is TRUE. See About caching .
<code>update_cache</code>	A logical whether to update cache. Default is FALSE. When set to TRUE it would force a fresh download of the source file.
<code>cache_dir</code>	A path to a cache directory. See About caching .
<code>verbose</code>	Logical, displays information. Useful for debugging, default is FALSE.

resolution	Resolution of the polygon. Values available are "3", "6.5" or "10".
domain	Possible values are "land", that includes only the ground part or the ground or "landsea", that includes both the ground and the related sea waters of the basin

Details

Metadata available on <https://github.com/rOpenSpain/mapSpain/tree/sianedata/>.

Value

A **sf** polygon object.

About caching

You can set your cache_dir with [esp_set_cache_dir\(\)](#).

Sometimes cached files may be corrupt. On that case, try re-downloading the data setting update_cache = TRUE.

If you experience any problem on download, try to download the corresponding .geojson file by any other method and save it on your cache_dir. Use the option verbose = TRUE for debugging the API query.

Source

IGN data via a custom CDN (see <https://github.com/rOpenSpain/mapSpain/tree/sianedata>).

See Also

Other natural: [esp_get_hypsobath\(\)](#), [esp_get_rivers\(\)](#)

Examples

```
hydroland <- esp_get_hydrobasin(domain = "land")
hydrolandsea <- esp_get_hydrobasin(domain = "landsea")

library(ggplot2)

ggplot(hydroland) +
  geom_sf(data = hydrolandsea, fill = "skyblue4", alpha = .4) +
  geom_sf(fill = "skyblue", alpha = .5) +
  geom_sf_text(aes(label = rotulo),
               size = 3, check_overlap = TRUE,
               fontface = "bold",
               family = "serif"
  ) +
  coord_sf(
    xlim = c(-9.5, 4.5),
    ylim = c(35, 44)
  ) +
```

```
theme_void()
```

`esp_get_hypsobath` *Get R href="https://CRAN.R-project.org/package=sfsf" polygons and lines with the hypsometry and bathymetry of Spain.*

Description

Loads a **sf** polygon or line object representing the hypsometry and bathymetry of Spain.

- **Hypsometry** represents the elevation and depth of features of the Earth's surface relative to mean sea level.
- **Bathymetry** is the measurement of the depth of water in oceans, rivers, or lakes.

Usage

```
esp_get_hypsobath(
  epsg = "4258",
  cache = TRUE,
  update_cache = FALSE,
  cache_dir = NULL,
  verbose = FALSE,
  resolution = "3",
  spatialtype = "area"
)
```

Arguments

<code>epsg</code>	projection of the map: 4-digit EPSG code . One of:
	<ul style="list-style-type: none"> • "4258": ETRS89 • "4326": WGS84 • "3035": ETRS89 / ETRS-LAEA • "3857": Pseudo-Mercator
<code>cache</code>	A logical whether to do caching. Default is TRUE. See About caching .
<code>update_cache</code>	A logical whether to update cache. Default is FALSE. When set to TRUE it would force a fresh download of the source file.
<code>cache_dir</code>	A path to a cache directory. See About caching .
<code>verbose</code>	Logical, displays information. Useful for debugging, default is FALSE.
<code>resolution</code>	Resolution of the shape. Values available are "3" or "6.5".
<code>spatialtype</code>	Spatial type of the output. Use "area" for polygons or "line" for lines.

Details

Metadata available on <https://github.com/rOpenSpain/mapSpain/tree/sianedata/>.

Value

A **sf** polygon or line object.

About caching

You can set your cache_dir with `esp_set_cache_dir()`.

Sometimes cached files may be corrupt. On that case, try re-downloading the data setting update_cache = TRUE.

If you experience any problem on download, try to download the corresponding .geojson file by any other method and save it on your cache_dir. Use the option verbose = TRUE for debugging the API query.

Source

IGN data via a custom CDN (see <https://github.com/rOpenSpain/mapSpain/tree/sianedata>).

See Also

Other natural: `esp_get_hydrobasin()`, `esp_get_rivers()`

Examples

```
# This code would produce a nice plot - It will take a few seconds to run
library(ggplot2)

hypsobath <- esp_get_hypsobath()

# Error on the data provided - There is an empty shape
# Remove:

hypsobath <- hypsobath[!sf::st_is_empty(hypsobath), ]

# Tints from Wikipedia
# https://en.wikipedia.org/wiki/Wikipedia:WikiProject\_Maps/Conventions/Topographic\_maps

bath_tints <- colorRampPalette(
  rev(
    c(
      "#D8F2FE", "#C6ECFF", "#B9E3FF",
      "#ACDBFB", "#A1D2F7", "#96C9F0",
      "#8DC1EA", "#84B9E3", "#79B2DE",
      "#71ABD8"
    )
  )
)

hypsotints <- colorRampPalette(
  rev(
    c(

```

```

    "#F5F4F2", "#E0DED8", "#CAC3B8", "#BAAE9A",
    "#AC9A7C", "#AA8753", "#B9985A", "#C3A76B",
    "#CAB982", "#D3CA9D", "#DED6A3", "#E8E1B6",
    "#EFEBBC", "#E1E4B5", "#D1D7AB", "#BDCC96",
    "#A8C68F", "#94BF8B", "#ACD0A5"
)
)
)

levels <- sort(unique(hypsobath$val_inf))

# Create palette
br_bath <- length(levels[levels < 0])
br_terrain <- length(levels) - br_bath

pal <- c(bath_tints((br_bath)), hyps_tints((br_terrain)))

# Plot Canary Islands
ggplot(hypsobath) +
  geom_sf(aes(fill = as.factor(val_inf)),
          color = NA
  ) +
  coord_sf(
    xlim = c(-18.6, -13),
    ylim = c(27, 29.5)
  ) +
  scale_fill_manual(values = pal) +
  guides(fill = guide_legend(
    title = "Elevation",
    direction = "horizontal",
    label.position = "bottom",
    title.position = "top",
    nrow = 1
  )) +
  theme(legend.position = "bottom")

# Plot Mainland
ggplot(hypsobath) +
  geom_sf(aes(fill = as.factor(val_inf)),
          color = NA
  ) +
  coord_sf(
    xlim = c(-9.5, 4.4),
    ylim = c(35.8, 44)
  ) +
  scale_fill_manual(values = pal) +
  guides(fill = guide_legend(
    title = "Elevation",
    reverse = TRUE,
    keyheight = .8
  ))

```

esp_get_munic Get municipalities of Spain as R href`https://CRAN.R-project.org/package=sf` polygons

Description

Returns municipalities of Spain as polygons at a specified scale.

- `esp_get_munic()` uses GISCO (Eurostat) as source. Please use `giscoR::gisco_attributions()`
- `esp_get_munic_siane()` uses CartoBase ANE as source, provided by Instituto Geografico Nacional (IGN), <http://www.ign.es/web/ign/portal>. Years available are 2005 up to today.

Usage

```
esp_get_munic(  
  year = "2019",  
  epsg = "4258",  
  cache = TRUE,  
  update_cache = FALSE,  
  cache_dir = NULL,  
  verbose = FALSE,  
  region = NULL,  
  munic = NULL,  
  moveCAN = TRUE  
)  
  
esp_get_munic_siane(  
  year = Sys.Date(),  
  epsg = "4258",  
  cache = TRUE,  
  update_cache = FALSE,  
  cache_dir = NULL,  
  verbose = FALSE,  
  resolution = 3,  
  region = NULL,  
  munic = NULL,  
  moveCAN = TRUE,  
  rawcols = FALSE  
)
```

Arguments

<code>year</code>	Release year. See Details for years available.
<code>epsg</code>	projection of the map: 4-digit EPSG code . One of: <ul style="list-style-type: none"> • "4258": ETRS89 • "4326": WGS84 • "3035": ETRS89 / ETRS-LAEA • "3857": Pseudo-Mercator
<code>cache</code>	A logical whether to do caching. Default is TRUE. See About caching .
<code>update_cache</code>	A logical whether to update cache. Default is FALSE. When set to TRUE it would force a fresh download of the source file.
<code>cache_dir</code>	A path to a cache directory. See About caching .
<code>verbose</code>	Logical, displays information. Useful for debugging, default is FALSE.
<code>region</code>	A vector of names and/or codes for provinces or NULL to get all the municipalities. See Details .
<code>munic</code>	A name or regex expression with the names of the required municipalities. NULL would not produce any filtering.
<code>moveCAN</code>	A logical TRUE/FALSE or a vector of coordinates <code>c(lat, lon)</code> . It places the Canary Islands close to Spain's mainland. Initial position can be adjusted using the vector of coordinates. See Displacing the Canary Islands .
<code>resolution</code>	Resolution of the polygon. Values available are "3", "6.5" or "10".
<code>rawcols</code>	Logical. Setting this to TRUE would add the raw columns of the dataset provided by IGN.

Details

The years available are:

- `esp_get_munic()`: year could be one of "2001", "2004", "2006", "2008", "2010", "2013" and any year between 2016 and 2019. See [giscoR::gisco_get_lau\(\)](#), [giscoR::gisco_get_communes\(\)](#).
- `esp_get_munic_siane()`: year could be passed as a single year ("YYYY" format, as end of year) or as a specific date ("YYYY-MM-DD" format). Historical information starts as of 2005.

When using `region` you can use and mix names and NUTS codes (levels 1, 2 or 3), ISO codes (corresponding to level 2 or 3) or "cpro" (see [esp_codelist](#)).

When calling a superior level (Province, Autonomous Community or NUTS1), all the municipalities of that level would be added.

Value

A **sf** polygon

About caching

You can set your `cache_dir` with `esp_set_cache_dir()`.

Sometimes cached files may be corrupt. On that case, try re-downloading the data setting `update_cache = TRUE`.

If you experience any problem on download, try to download the corresponding `.geojson` file by any other method and save it on your `cache_dir`. Use the option `verbose = TRUE` for debugging the API query.

Displacing the Canary Islands

While `moveCAN` is useful for visualization, it would alter the actual geographic position of the Canary Islands. When using the output for spatial analysis or using tiles (e.g. with `esp_getTiles()` or `addProviderEspTiles()`) this option should be set to `FALSE` in order to get the actual coordinates, instead of the modified ones. See also `esp_move_can()` for displacing stand-alone `sf` objects.

Source

GISCO API

IGN data via a custom CDN (see <https://github.com/rOpenSpain/mapSpain/tree/sianedata>).

See Also

`giscoR::gisco_get_lau()`, `base::regex()`.

Other political: `esp_codelist`, `esp_get_can_box()`, `esp_get_capimun()`, `esp_get_ccaa()`, `esp_get_comarca()`, `esp_get_country()`, `esp_get_gridmap`, `esp_get_nuts()`, `esp_get_prov()`, `esp_get_simpl_prov()`

Other municipalities: `esp_get_capimun()`, `esp_munic_sf`

Examples

```
# Get munics
Base <- esp_get_munic(year = "2019", region = "Castilla y Leon")

# Provs for delimiting
provs <- esp_get_prov(prov = "Castilla y Leon")

# Load population data
data("pobmun19")

# Arrange and create breaks

Base_pop <- merge(Base, pobmun19,
  by = c("cpro", "cmun"),
  all.x = TRUE
)

br <- sort(c(
  0, 50, 100, 200, 500,
  1000, 5000, 50000, 100000,
```

```

Inf
))

Base_pop$cuts <- cut(Base_pop$pob19, br, dig.lab = 20)

# Plot
library(ggplot2)

ggplot(Base_pop) +
  geom_sf(aes(fill = cuts), color = NA) +
  geom_sf(data = provs, fill = NA, color = "grey70") +
  scale_fill_manual(values = hcl.colors(length(br), "cividis")) +
  labs(
    title = "Population in Castilla y Leon",
    subtitle = "INE, 2019",
    fill = "Persons"
  ) +
  theme_void()

```

esp_get_nuts

Get NUTS of Spain as R href="https://CRAN.R-project.org/package=sfsf"
polygons and points

Description

Returns **NUTS regions of Spain** as polygons and points at a specified scale, as provided by **GISCO** (Geographic Information System of the Commission, depending of Eurostat).

NUTS are provided at three different levels:

- "**0
- "**1
- "**2
- "**3********

Usage

```

esp_get_nuts(
  year = "2016",
  epsg = "4258",
  cache = TRUE,
  update_cache = FALSE,
  cache_dir = NULL,
  verbose = FALSE,
  resolution = "01",
  spatialtype = "RG",

```

```

    region = NULL,
    nuts_level = "all",
    moveCAN = TRUE
)

```

Arguments

year	Release year of the file. One of "2003", "2006", "2010", "2013", "2016" or "2021".
epsg	projection of the map: 4-digit EPSG code . One of: <ul style="list-style-type: none"> "4258": ETRS89 "4326": WGS84 "3035": ETRS89 / ETRS-LAEA "3857": Pseudo-Mercator
cache	A logical whether to do caching. Default is TRUE. See About caching .
update_cache	A logical whether to update cache. Default is FALSE. When set to TRUE it would force a fresh download of the source file.
cache_dir	A path to a cache directory. See About caching .
verbose	Logical, displays information. Useful for debugging, default is FALSE.
resolution	Resolution of the geospatial data. One of <ul style="list-style-type: none"> "60": 1:60million "20": 1:20million "10": 1:10million "03": 1:3million "01": 1:1million
spatialtype	Type of geometry to be returned: <ul style="list-style-type: none"> "LB": Labels - point object. "RG": Regions - polygon object.
region	Optional. A vector of region names, NUTS or ISO codes (see esp_dict_region_code()).
nuts_level	NUTS level. One of "0" (Country-level), "1", "2" or "3". See Description .
moveCAN	A logical TRUE/FALSE or a vector of coordinates c(lat, lon). It places the Canary Islands close to Spain's mainland. Initial position can be adjusted using the vector of coordinates. See Displacing the Canary Islands .

Value

A **sf** object specified by spatialtype.

About caching

You can set your cache_dir with [esp_set_cache_dir\(\)](#).

Sometimes cached files may be corrupt. On that case, try re-downloading the data setting update_cache = TRUE.

If you experience any problem on download, try to download the corresponding .geojson file by any other method and save it on your cache_dir. Use the option verbose = TRUE for debugging the API query.

Displacing the Canary Islands

While `moveCAN` is useful for visualization, it would alter the actual geographic position of the Canary Islands. When using the output for spatial analysis or using tiles (e.g. with `esp_getTiles()` or `addProviderEspTiles()`) this option should be set to FALSE in order to get the actual coordinates, instead of the modified ones. See also `esp_move_can()` for displacing stand-alone `sf` objects.

Note

Please check the download and usage provisions on `giscoR::gisco_attributions()`

Source

[GISCO API](#)

See Also

`giscoR::gisco_get_nuts()`, `esp_dict_region_code()`.

Other political: `esp_codelist`, `esp_get_can_box()`, `esp_get_capimun()`, `esp_get_ccaa()`, `esp_get_comarca()`, `esp_get_country()`, `esp_get_gridmap`, `esp_get_munic()`, `esp_get_prov()`, `esp_get_simpl_prov()`

Other nuts: `esp_nuts.sf`

Examples

```
NUTS1 <- esp_get_nuts(nuts_level = 1, moveCAN = TRUE)

library(ggplot2)

ggplot(NUTS1) +
  geom_sf() +
  labs(
    title = "NUTS1: Displacing Canary Islands",
    caption = giscoR::gisco_attributions()
  )

NUTS1_alt <- esp_get_nuts(nuts_level = 1, moveCAN = c(15, 0))

ggplot(NUTS1_alt) +
  geom_sf() +
  labs(
    title = "NUTS1: Displacing Canary Islands",
    subtitle = "to the right",
    caption = giscoR::gisco_attributions()
  )

NUTS1_orig <- esp_get_nuts(nuts_level = 1, moveCAN = FALSE)
```

```

ggplot(NUTS1_orig) +
  geom_sf() +
  labs(
    title = "NUTS1",
    subtitle = "Canary Islands on the true location",
    caption = giscoR::gisco_attributions()
  )

AndOriental <-
  esp_get_nuts(region = c("Almeria", "Granada", "Jaen", "Malaga"))

ggplot(AndOriental) +
  geom_sf()

RandomRegions <- esp_get_nuts(region = c("ES1", "ES300", "ES51"))

ggplot(RandomRegions) +
  geom_sf() +
  labs(title = "Random Regions")

MixingCodes <- esp_get_nuts(region = c("ES4", "ES-PV", "Valencia"))

ggplot(MixingCodes) +
  geom_sf() +
  labs(title = "Mixing Codes")

```

esp_get_prov

Get Provinces of Spain as R href="https://CRAN.R-project.org/package=sf" polygons and points

Description

Returns **provinces of Spain** as polygons and points at a specified scale.

- **esp_get_prov()** uses GISCO (Eurostat) as source. Please use `giscoR::gisco_attributions()`
- **esp_get_prov_siane()** uses CartoBase ANE as source, provided by Instituto Geografico Nacional (IGN), <http://www.ign.es/web/ign/portal>. Years available are 2005 up to today.

Usage

```
esp_get_prov(prov = NULL, moveCAN = TRUE, ...)
```

```
esp_get_prov_siane(
  prov = NULL,
  year = Sys.Date(),
  epsg = "4258",
  cache = TRUE,
  update_cache = FALSE,
  cache_dir = NULL,
  verbose = FALSE,
  resolution = "3",
  moveCAN = TRUE,
  rawcols = FALSE
)
```

Arguments

<code>prov</code>	A vector of names and/or codes for provinces or <code>NULL</code> to get all the provinces. See Details .
<code>moveCAN</code>	A logical <code>TRUE/FALSE</code> or a vector of coordinates <code>c(lat, lon)</code> . It places the Canary Islands close to Spain's mainland. Initial position can be adjusted using the vector of coordinates. See Displacing the Canary Islands .
<code>...</code>	Arguments passed on to <code>esp_get_nuts</code>
<code>spatialtype</code>	Type of geometry to be returned: <ul style="list-style-type: none"> • "LB": Labels - point object. • "RG": Regions - polygon object.
<code>year</code>	Release year. See <code>esp_get_nuts()</code> for <code>esp_get_prov()</code> and Details for <code>esp_get_prov_siane()</code>
<code>epsg</code>	projection of the map: 4-digit EPSG code . One of: <ul style="list-style-type: none"> • "4258": ETRS89 • "4326": WGS84 • "3035": ETRS89 / ETRS-LAEA • "3857": Pseudo-Mercator
<code>cache</code>	A logical whether to do caching. Default is <code>TRUE</code> . See About caching .
<code>update_cache</code>	A logical whether to update cache. Default is <code>FALSE</code> . When set to <code>TRUE</code> it would force a fresh download of the source file.
<code>cache_dir</code>	A path to a cache directory. See About caching .
<code>verbose</code>	Logical, displays information. Useful for debugging, default is <code>FALSE</code> .
<code>resolution</code>	Resolution of the polygon. Values available are 3, 6.5 or 10.
<code>rawcols</code>	Logical. Setting this to <code>TRUE</code> would add the raw columns of the dataset provided by IGN.

Details

When using `prov` you can use and mix names and NUTS codes (levels 1, 2 or 3), ISO codes (corresponding to level 2 or 3) or "cpro" (see `esp_codelist`).

Ceuta and Melilla are considered as provinces on this dataset.

When calling a superior level (Autonomous Community or NUTS1) , all the provinces of that level would be added.

On [esp_get_prov_siane\(\)](#), year could be passed as a single year ("YYYY" format, as end of year) or as a specific date ("YYYY-MM-DD" format). Historical information starts as of 2005.

Value

A **sf** object specified by spatialtype.

About caching

You can set your cache_dir with [esp_set_cache_dir\(\)](#).

Sometimes cached files may be corrupt. On that case, try re-downloading the data setting update_cache = TRUE.

If you experience any problem on download, try to download the corresponding .geojson file by any other method and save it on your cache_dir. Use the option verbose = TRUE for debugging the API query.

Displacing the Canary Islands

While moveCAN is useful for visualization, it would alter the actual geographic position of the Canary Islands. When using the output for spatial analysis or using tiles (e.g. with [esp_getTiles\(\)](#) or [addProviderEspTiles\(\)](#)) this option should be set to FALSE in order to get the actual coordinates, instead of the modified ones. See also [esp_move_can\(\)](#) for displacing stand-alone **sf** objects.

Source

IGN data via a custom CDN (see <https://github.com/rOpenSpain/mapSpain/tree/sianedata>).

See Also

Other political: [esp_codelist](#), [esp_get_can_box\(\)](#), [esp_get_capimun\(\)](#), [esp_get_ccaa\(\)](#), [esp_get_comarca\(\)](#), [esp_get_country\(\)](#), [esp_get_gridmap](#), [esp_get_munic\(\)](#), [esp_get_nuts\(\)](#), [esp_get_simpl_prov\(\)](#)

Examples

```
prov <- esp_get_prov()

library(ggplot2)

ggplot(prov) +
  geom_sf() +
  theme_void()

# Random Provinces

Random <-
  esp_get_prov(prov = c(
    "Zamora",
```

```

    "Palencia",
    "ES-GR",
    "ES521",
    "01"
  )))

ggplot(Random) +
  geom_sf(aes(fill = codauto), show.legend = FALSE, alpha = 0.5) +
  scale_fill_manual(values = hcl.colors(
    nrow(Random), "Spectral"
  )) +
  theme_minimal()

# All Provinces of a Zone plus an addition

Mix <- esp_get_prov(prov = c(
  "Noroeste",
  "Castilla y Leon", "La Rioja"
))
Mix$CCAA <- esp_dict_region_code(
  Mix$codauto,
  origin = "codauto"
)
ggplot(Mix) +
  geom_sf(aes(fill = CCAA), alpha = 0.5) +
  scale_fill_discrete(type = hcl.colors(5, "Temps")) +
  theme_classic()

# ISO codes available

allprovs <- esp_get_prov()

ggplot(allprovs) +
  geom_sf(fill = NA) +
  geom_sf_text(aes(label = iso2.prov.code),
    check_overlap = TRUE,
    fontface = "bold"
  ) +
  theme_void()

```

Description

Loads a **sf** lines or point object representing the nodes and railway lines of Spain.

Usage

```
esp_get_railway(  
  year = Sys.Date(),  
  epsg = "4258",  
  cache = TRUE,  
  update_cache = FALSE,  
  cache_dir = NULL,  
  verbose = FALSE,  
  spatialtype = "line"  
)
```

Arguments

year	Release year.
epsg	projection of the map: 4-digit EPSG code . One of: <ul style="list-style-type: none">• "4258": ETRS89• "4326": WGS84• "3035": ETRS89 / ETRS-LAEA• "3857": Pseudo-Mercator
cache	A logical whether to do caching. Default is TRUE. See About caching .
update_cache	A logical whether to update cache. Default is FALSE. When set to TRUE it would force a fresh download of the source file.
cache_dir	A path to a cache directory. See About caching .
verbose	Logical, displays information. Useful for debugging, default is FALSE.
spatialtype	Spatial type of the output. Use "line" for extracting the railway as lines and "point" for extracting stations.

Value

A **sf** line or point object.

About caching

You can set your cache_dir with [esp_set_cache_dir\(\)](#).

Sometimes cached files may be corrupt. On that case, try re-downloading the data setting update_cache = TRUE.

If you experience any problem on download, try to download the corresponding .geojson file by any other method and save it on your cache_dir. Use the option verbose = TRUE for debugging the API query.

Source

IGN data via a custom CDN (see <https://github.com/rOpenSpain/mapSpain/tree/sianedata>).

See Also

Other infrastructure: [esp_get_roads\(\)](#)

Examples

```

provs <- esp_get_prov()
ccaa <- esp_get_ccaa()

# Railways
rails <- esp_get_railway()

# Stations
stations <- esp_get_railway(spatialtype = "point")

# Map

library(ggplot2)

ggplot(provs) +
  geom_sf(fill = "grey99", color = "grey50") +
  geom_sf(data = ccaa, fill = NA) +
  geom_sf(
    data = rails, aes(color = tipo),
    show.legend = FALSE, linewidth = 1.5
  ) +
  geom_sf(
    data = stations,
    color = "red", alpha = 0.5
  ) +
  coord_sf(
    xlim = c(-7.5, -2.5),
    ylim = c(38, 41)
  ) +
  scale_color_manual(values = hcl.colors(
    length(unique(rails$tipo)), "viridis"
  )) +
  theme_minimal()

```

[esp_get_rivers](#)

Get R <https://CRAN.R-project.org/package=sfsf> polygon and lines of rivers, channels and other wetlands of Spain

Description

Loads a **sf** polygon or line object representing rivers, channels, reservoirs and other wetlands of Spain

Usage

```
esp_get_rivers(  
  epsg = "4258",  
  cache = TRUE,  
  update_cache = FALSE,  
  cache_dir = NULL,  
  verbose = FALSE,  
  resolution = "3",  
  spatialtype = "line",  
  name = NULL  
)
```

Arguments

epsg	projection of the map: 4-digit EPSG code . One of: <ul style="list-style-type: none">• "4258": ETRS89• "4326": WGS84• "3035": ETRS89 / ETRS-LAEA• "3857": Pseudo-Mercator
cache	A logical whether to do caching. Default is TRUE. See About caching .
update_cache	A logical whether to update cache. Default is FALSE. When set to TRUE it would force a fresh download of the source file.
cache_dir	A path to a cache directory. See About caching .
verbose	Logical, displays information. Useful for debugging, default is FALSE.
resolution	Resolution of the polygon. Values available are "3", "6.5" or "10".
spatialtype	Spatial type of the output. Use "area" for polygons or "line" for lines.
name	Optional. A character or regex expression with the name of the element(s) to be extracted.

Details

Metadata available on <https://github.com/rOpenSpain/mapSpain/tree/sianedata/>.

Value

A **sf** polygon or line object.

Source

IGN data via a custom CDN (see <https://github.com/rOpenSpain/mapSpain/tree/sianedata>).

See Also

Other natural: [esp_get_hydrobasin\(\)](#), [esp_get_hypsobath\(\)](#)

Examples

```
# Use of regex

regex1 <- esp_get_rivers(name = "Tajo|Segura")
unique(regex1$rotulo)

regex2 <- esp_get_rivers(name = "Tajo$| Segura")
unique(regex2$rotulo)

# See the difference

# Rivers in Spain
shapeEsp <- esp_get_country(moveCAN = FALSE)

MainRivers <-
  esp_get_rivers(name = "Tajo$|Ebro$|Ebre$|Duero|Guadiana$|Guadalquivir")

sf::st_bbox(MainRivers)
library(ggplot2)

ggplot(shapeEsp) +
  geom_sf() +
  geom_sf(data = MainRivers, color = "skyblue", linewidth = 2) +
  coord_sf(
    xlim = c(-7.5, 1),
    ylim = c(36.8, 43)
  ) +
  theme_void()

# Wetlands in South-West Andalucia
and <- esp_get_prov(c("Huelva", "Sevilla", "Cadiz"))
Wetlands <- esp_get_rivers(spatialtype = "area")

ggplot(and) +
  geom_sf() +
  geom_sf(
    data = Wetlands, fill = "skyblue",
    color = "skyblue", alpha = 0.5
  ) +
  coord_sf(
    xlim = c(-7.5, -4.5),
    ylim = c(36, 38.5)
  ) +
  theme_void()
```

esp_get_roads	<i>Get R href="https://CRAN.R-project.org/package=sfsf" lines of the roads of Spain</i>
---------------	---

Description

Loads a **sf** line object representing the main roads of Spain.

Usage

```
esp_get_roads(
  year = Sys.Date(),
  epsg = "4258",
  cache = TRUE,
  update_cache = FALSE,
  cache_dir = NULL,
  verbose = FALSE,
  moveCAN = TRUE
)
```

Arguments

year	Release year. See Details for years available.
epsg	projection of the map: 4-digit EPSG code . One of: <ul style="list-style-type: none"> • "4258": ETRS89 • "4326": WGS84 • "3035": ETRS89 / ETRS-LAEA • "3857": Pseudo-Mercator
cache	A logical whether to do caching. Default is TRUE. See About caching .
update_cache	A logical whether to update cache. Default is FALSE. When set to TRUE it would force a fresh download of the source file.
cache_dir	A path to a cache directory. See About caching .
verbose	Logical, displays information. Useful for debugging, default is FALSE.
moveCAN	A logical TRUE/FALSE or a vector of coordinates c(lat, lon). It places the Canary Islands close to Spain's mainland. Initial position can be adjusted using the vector of coordinates. See Displacing the Canary Islands .

Details

year could be passed as a single year ("YYYY" format, as end of year) or as a specific date ("YYYY-MM-DD" format).

Value

A **sf** line object.

About caching

You can set your `cache_dir` with [esp_set_cache_dir\(\)](#).

Sometimes cached files may be corrupt. On that case, try re-downloading the data setting `update_cache = TRUE`.

If you experience any problem on download, try to download the corresponding `.geojson` file by any other method and save it on your `cache_dir`. Use the option `verbose = TRUE` for debugging the API query.

Displacing the Canary Islands

While moveCAN is useful for visualization, it would alter the actual geographic position of the Canary Islands. When using the output for spatial analysis or using tiles (e.g. with [esp_getTiles\(\)](#) or [addProviderEspTiles\(\)](#)) this option should be set to FALSE in order to get the actual coordinates, instead of the modified ones. See also [esp_move_can\(\)](#) for displacing stand-alone `sf` objects.

Source

IGN data via a custom CDN (see <https://github.com/rOpenSpain/mapSpain/tree/sianedata>).

See Also

Other infrastructure: [esp_get_railway\(\)](#)

Examples

```
country <- esp_get_country()
Roads <- esp_get_roads()

library(ggplot2)

ggplot(country) +
  geom_sf(fill = "grey90") +
  geom_sf(data = Roads, aes(color = tipo), show.legend = "line") +
  scale_color_manual(
    values = c("#003399", "#003399", "#ff0000", "#ffff00")
  ) +
  guides(color = guide_legend(direction = "vertical")) +
  theme_minimal() +
  labs(color = "Road type") +
  theme(legend.position = "bottom")
```

esp_get_simpl_prov	<i>Get a simplified map of provinces and autonomous communities of Spain</i>
--------------------	--

Description

Loads a simplified map (**sf** object) with the boundaries of the provinces or autonomous communities of Spain, as provided by the **INE** (Instituto Nacional de Estadística).

Usage

```
esp_get_simpl_prov(
  prov = NULL,
  update_cache = FALSE,
  cache_dir = NULL,
  verbose = FALSE
)

esp_get_simpl_ccaa(
  ccaa = NULL,
  update_cache = FALSE,
  cache_dir = NULL,
  verbose = FALSE
)
```

Arguments

prov	A vector of names and/or codes for provinces or NULL to get all the provinces. See Details .
update_cache	A logical whether to update cache. Default is FALSE . When set to TRUE it would force a fresh download of the source file.
cache_dir	A path to a cache directory. See About caching .
verbose	Logical, displays information. Useful for debugging, default is FALSE .
ccaa	A vector of names and/or codes for autonomous communities or NULL to get all the autonomous communities. See Details .

Details

Results are provided **without CRS**, as provided on source.

You can use and mix names, ISO codes, "codauto"/"cpro" codes (see [esp_codelist](#)) and NUTS codes of different levels.

When using a code corresponding of a higher level (e.g. `esp_get_simpl_prov("Andalucia")`) all the corresponding units of that level are provided (in this case , all the provinces of Andalucia).

Value

A **sf** POLYGON object.

About caching

You can set your cache_dir with [esp_set_cache_dir\(\)](#).

Sometimes cached files may be corrupt. On that case, try re-downloading the data setting update_cache = TRUE.

If you experience any problem on download, try to download the corresponding .geojson file by any other method and save it on your cache_dir. Use the option verbose = TRUE for debugging the API query.

Source

INE: PC_Axis files

See Also

[esp_get_hex_prov\(\)](#), [esp_get_hex_ccaa\(\)](#)

Other political: [esp_codelist](#), [esp_get_can_box\(\)](#), [esp_get_capimun\(\)](#), [esp_get_ccaa\(\)](#), [esp_get_comarca\(\)](#), [esp_get_country\(\)](#), [esp_get_gridmap](#), [esp_get_munic\(\)](#), [esp_get_nuts\(\)](#), [esp_get_prov\(\)](#)

Examples

```
prov_simp <- esp_get_simpl_prov()

library(ggplot2)

ggplot(prov_simp) +
  geom_sf(aes(fill = ine.ccaa.name)) +
  labs(fill = "CCAA")

# Provs of Single CCAA

and_simple <- esp_get_simpl_prov("Andalucia")

ggplot(and_simple) +
  geom_sf()

# CCAAs

ccaa_simp <- esp_get_simpl_ccaa()

ggplot(ccaa_simp) +
  geom_sf() +
  geom_sf_text(aes(label = ine.ccaa.name), check_overlap = TRUE)
```

esp_make_provider *Create a custom tile provider*

Description

Helper function for [esp_getTiles\(\)](#) that helps to create a custom provider.

Usage

```
esp_make_provider(id, q, service, layers, ...)
```

Arguments

id	An identifier for the user. Would be used also for identifying cached tiles.
q	The base url of the service
service	The type of tile service, either "WMS" or "WMPS".
layers	The name of the layer to retrieve
...	Additional parameters to the query, like version, format, crs/srs, style, ... depending on the capabilities of the service.

Details

This function is meant to work with services provided as of the [OGC Standard](#).

Note that:

- **mapSpain** would not provide advice on the parameter q to be provided.
- Currently, on **WMPS** requests only services with `tilematrixset=GoogleMapsCompatible` are supported.

Value

A named list with two elements id and q.

See Also

[esp_getTiles\(\)](#).

For a list of potential providers from Spain check [IDEE Directory](#).

Other imagery utilities: `addProviderEspTiles()`, `esp_getTiles()`, `esp_tiles_providers`

Examples

```
## Not run:
# This script downloads tiles to your local machine
# Run only if you are online

custom_wms <- esp_make_provider(
  id = "an_id_for_caching",
  q = "https://idecyl.jcyl.es/geoserver/ge/wms?",
  service = "WMS",
  layers = "geolog_cyl_litologia"
)

x <- esp_get_ccaa("Castilla y León", epsg = 3857)

mytile <- esp_getTiles(x, type = custom_wms)

tidyterra::autoplot(mytile) +
  ggplot2::geom_sf(data = x, fill = NA)

## End(Not run)
```

esp_move_can

Displace a R href="https://CRAN.R-project.org/package=sfsf" object located in the Canary Islands

Description

Helper function to displace an external **sf** object (potentially representing a location in the Canary Islands) to align it with the objects provided by **sf** with the option moveCAN = TRUE.

Usage

```
esp_move_can(x, moveCAN = TRUE)
```

Arguments

- | | |
|---------|--|
| x | An sf object. It may be sf or sfc object. |
| moveCAN | A logical TRUE/FALSE or a vector of coordinates c(lat, lon). |

Details

This is a helper function that intends to ease the representation of objects located in the Canary Islands that have been obtained from other sources rather than the package **mapSpain**.

Value

A **sf** object of the same class and same CRS than x but displaced accordingly.

See Also

Other helper: [esp_check_access\(\)](#)
Other Canary Islands: [esp_get_can_box\(\)](#)

Examples

```
library(sf)
teide <- data.frame(
  name = "Teide Peak",
  lon = -16.6437593,
  lat = 28.2722883
)
teide_sf <- st_as_sf(teide, coords = c("lon", "lat"), crs = 4326)

# If we use any mapSpain produced object with moveCAN = TRUE...

esp <- esp_get_country(moveCAN = c(13, 0))

library(ggplot2)

ggplot(esp) +
  geom_sf() +
  geom_sf(data = teide_sf, color = "red") +
  labs(
    title = "Canary Islands displaced",
    subtitle = "But not the external Teide object"
  )

# But we can

teide_sf_disp <- esp_move_can(teide_sf, moveCAN = c(13, 0))

ggplot(esp) +
  geom_sf() +
  geom_sf(data = teide_sf_disp, color = "red") +
  labs(
    title = "Canary Islands displaced",
    subtitle = "And also the external Teide object"
  )
```

Description

A **sf** object including all municipalities of Spain as provided by GISCO (2019 version).

Format

A sf object (resolution: 1:1million, EPSG:4258) object with 8,131 rows and columns:

codauto INE code of the autonomous community.

ine.ccaa.name INE name of the autonomous community.

cpro INE code of the province.

ine.prov.name INE name of the province.

cmun INE code of the municipality.

name Name of the municipality.

LAU_CODE LAU Code (GISCO) of the municipality. This is a combination of **cpro** and **cmun**, aligned with INE coding scheme.

geometry geometry field.

Source

<https://ec.europa.eu/eurostat/web/gisco/geodata/reference-data/>, LAU 2019 data.

See Also

[esp_get_munic\(\)](#).

Other datasets: [esp_codelist](#), [esp_nuts.sf](#), [esp_tiles_providers](#), [pobmun19](#)

Other municipalities: [esp_get_capimun\(\)](#), [esp_get_munic\(\)](#)

Examples

```
data("esp_munic.sf")

teruel_cpro <- esp_dict_region_code("Teruel", destination = "cpro")

teruel_sf <- esp_munic.sf[esp_munic.sf$cpro == teruel_cpro, ]
teruel_city <- teruel_sf[teruel_sf$name == "Teruel", ]

# Plot

library(ggplot2)

ggplot(teruel_sf) +
  geom_sf(fill = "#FDFBEA") +
  geom_sf(data = teruel_city, aes(fill = name)) +
  scale_fill_manual(
    values = "#C12838",
    labels = "City of Teruel"
  ) +
  labs(
```

```

    fill = "",
    title = "Municipalities of Teruel"
) +
theme_minimal() +
theme(
  text = element_text(face = "bold"),
  panel.background = element_rect(colour = "black"),
  panel.grid = element_blank(),
  legend.position = c(.2, .95)
)

```

`esp_nuts_sf`*All NUTS POLYGON object of Spain*

Description

A **sf** object including all NUTS levels of Spain as provided by GISCO (2016 version).

Format

A sf object (resolution: 1:1million, EPSG:4258) with 86 rows and columns:

LEVL_CODE NUTS level code (0,1,2,3)

NUTS_ID NUTS identifier

URBN_TYPE Urban Type, see Details

CNTR_CODE Eurostat Country code ES

NAME_LATN NUTS name on Latin characters

NUTS_NAME NUTS name on local alphabet

MOUNT_TYPE Mount Type, see Details

COAST_TYPE Coast Type, see Details

FID FID

geometry geometry field

Details

MOUNT_TYPE: Mountain typology:

- 1: More than 50 % of the surface is covered by topographic mountain areas.
- 2: More than 50 % of the regional population lives in topographic mountain areas.
- 3: More than 50 % of the surface is covered by topographic mountain areas and where more than 50 % of the regional population lives in these mountain areas.
- 4: Non-mountain region / other regions.
- 0: No classification provided

URBN_TYPE: Urban-rural typology:

- 1: Predominantly urban region.
- 2: Intermediate region.
- 3: Predominantly rural region.
- 0: No classification provided

COAST_TYPE: Coastal typology:

- 1: Coastal (on coast).
- 2: Coastal (less than 50% of population living within 50 km. of the coastline).
- 3: Non-coastal region.
- 0: No classification provided

Source

<https://gisco-services.ec.europa.eu/distribution/v2/nuts/>, file NUTS_RG_20M_2016_4326.geojson.

See Also

Other datasets: [esp_codelist](#), [esp_munic.sf](#), [esp_tiles_providers](#), [pobmun19](#)

Other nuts: [esp_get_nuts\(\)](#)

Examples

```
data("esp_nuts.sf")

nuts <- esp_nuts.sf

# Select NUTS 3
nuts3 <- esp_nuts.sf[esp_nuts.sf$LEVL_CODE == 3, ]

# Combine with full shape

spain <- esp_get_country(moveCAN = FALSE)

# Plot Urban Type: See
# https://ec.europa.eu/eurostat/web/rural-development/methodology

library(ggplot2)

nuts3$URBN_TYPE_cat <- as.factor(nuts3$URBN_TYPE)

levels(nuts3$URBN_TYPE_cat)
levels(nuts3$URBN_TYPE_cat) <- c("Urban", "Intermediate", "Rural")

ggplot(nuts3) +
  geom_sf(aes(fill = URBN_TYPE_cat), linewidth = .1) +
  scale_fill_manual(values = c("grey80", "#FFC183", "#68AC20")) +
  labs(
    title = "NUTS3 levels of Spain",
    fill = "Urban topology"
```

```
) +
  theme_linedraw() +
  theme(
    legend.position = c(.8, .2)
  )
```

esp_set_cache_dir *Set your R href`https://CRAN.R-project.org/package=mapSpain` mapSpain cache dir*

Description

This function will store your `cache_dir` path on your local machine and would load it for future sessions. Type `Sys.getenv("MAPSPAIN_CACHE_DIR")` to find your cached path.

Alternatively, you can store the `cache_dir` manually with the following options:

- Run `Sys.setenv(MAPSPAIN_CACHE_DIR = "cache_dir")`. You would need to run this command on each session (Similar to `install = FALSE`).
- Set `options(mapSpain_cache_dir = "cache_dir")`. Similar to the previous option. This is **not recommended any more**, and it is provided for backwards compatibility purposes.
- Write this line on your `.Renvironment` file: `MAPSPAIN_CACHE_DIR = "value_for_cache_dir"` (same behavior than `install = TRUE`). This would store your `cache_dir` permanently.

Usage

```
esp_set_cache_dir(
  cache_dir,
  overwrite = FALSE,
  install = FALSE,
  verbose = TRUE
)
```

Arguments

<code>cache_dir</code>	A path to a cache directory. On missing value the function would store the cached files on a temporary dir (See <code>base::tempdir()</code>).
<code>overwrite</code>	If this is set to TRUE, it will overwrite an existing <code>MAPSPAIN_CACHE_DIR</code> that you already have in local machine.
<code>install</code>	if TRUE, will install the key in your local machine for use in future sessions. Defaults to FALSE. If <code>cache_dir</code> is FALSE this parameter is set to FALSE automatically.
<code>verbose</code>	Logical, displays information. Useful for debugging, default is FALSE.

Value

An (invisible) character with the path to your `cache_dir`.

See Also

[rapdirs::user_config_dir\(\)](#)

Other cache utilities: [esp_clear_cache\(\)](#), [esp_detect_cache_dir\(\)](#)

Examples

```
# Don't run this! It would modify your current state
## Not run:
esp_set_cache_dir(verbose = TRUE)

## End(Not run)

Sys.getenv("MAPSPAIN_CACHE_DIR")
```

esp_tiles_providers *List with information of Public WMS and WMTS of Spain*

Description

A named list of length 102 containing the parameters of the url information of different public WMS and WMTS providers of Spain.

Implementation of javascript plugin [leaflet-providersESP v1.3.3](#).

Format

A named list of the providers available with the following structure:

- Each item of the list is named with the provider alias.
- Each element of the list contains two nested named lists:
 - static with the parameters to get static tiles plus an additional item named attribution.
 - leaflet with additional parameters to be passed onto [addProviderEspTiles\(\)](#).

Details

Providers available to be passed to type on [esp_getTiles\(\)](#) are:

- "IDErioja"
- "IDErioja.Base"
- "IDErioja.Relieve"
- "IDErioja.Claro"
- "IDErioja.Oscuro"
- "IGNBase"
- "IGNBase.Todo"
- "IGNBase.Gris"

- "IGNBase.TodoNoFondo"
- "IGNBase.Orto"
- "MDT"
- "MDT.Elevaciones"
- "MDT.Relieve"
- "MDT.CurvasNivel"
- "MDT.SpotElevation"
- "PNOA"
- "PNOA.MaximaActualidad"
- "PNOA.Mosaico"
- "OcupacionSuelo"
- "OcupacionSuelo.Ocupacion"
- "OcupacionSuelo.Usos"
- "LiDAR"
- "MTN"
- "Geofisica"
- "Geofisica.Terremotos10dias"
- "Geofisica.Terremotos30dias"
- "Geofisica.Terremotos365dias"
- "Geofisica.ObservedEvents"
- "Geofisica.HazardArea"
- "VigilanciaVolcanica"
- "VigilanciaVolcanica.ErupcionesHistoricas"
- "CaminoDeSantiago"
- "CaminoDeSantiago.CaminoFrances"
- "CaminoDeSantiago.CaminosFrancia"
- "CaminoDeSantiago.CaminosGalicia"
- "CaminoDeSantiago.CaminosDelNorte"
- "CaminoDeSantiago.CaminosAndaluces"
- "CaminoDeSantiago.CaminosCentro"
- "CaminoDeSantiago.CaminosEste"
- "CaminoDeSantiago.CaminosCatalanes"
- "CaminoDeSantiago.CaminosSureste"
- "CaminoDeSantiago.CaminosInsulares"
- "CaminoDeSantiago.CaminosPortugueses"
- "Catastro"
- "Catastro.Catastro"

- "Catastro.Parcela"
- "Catastro.CadastralParcel"
- "Catastro.CadastralZoning"
- "Catastro.Address"
- "Catastro.Building"
- "Catastro.BuildingPart"
- "Catastro.AdministrativeBoundary"
- "Catastro.AdministrativeUnit"
- "RedTransporte"
- "RedTransporte.Carreteras"
- "RedTransporte.Ferroviario"
- "RedTransporte.Aerodromo"
- "RedTransporte.AreaServicio"
- "RedTransporte.EstacionesFerroviario"
- "RedTransporte.Puertos"
- "Cartociudad"
- "Cartociudad.CodigosPostales"
- "Cartociudad.Direcciones"
- "NombresGeograficos"
- "UnidadesAdm"
- "UnidadesAdm.Limites"
- "UnidadesAdm.Unidades"
- "Hidrografia"
- "Hidrografia.MasaAgua"
- "Hidrografia.Cuencas"
- "Hidrografia.Subcuencas"
- "Hidrografia.POI"
- "Hidrografia.ManMade"
- "Hidrografia.LineaCosta"
- "Hidrografia.Rios"
- "Hidrografia.Humedales"
- "Militar"
- "Militar.CEGET1M"
- "Militar.CEGETM7814"
- "Militar.CEGETM7815"
- "Militar.CEGETM682"
- "Militar.CECAF1M"

- "ADIF"
- "ADIF.Vias"
- "ADIF.Nodos"
- "ADIF.Estaciones"
- "LimitesMaritimos"
- "LimitesMaritimos.LimitesMaritimos"
- "LimitesMaritimos.LineasBase"
- "Copernicus"
- "Copernicus.Forest"
- "Copernicus.ForestLeaf"
- "Copernicus.WaterWet"
- "Copernicus.SoilSeal"
- "Copernicus.GrassLand"
- "Copernicus.RiparianGreen"
- "Copernicus.RiparianLandCover"
- "Copernicus.Natura2k"
- "Copernicus.UrbanAtlas"
- "ParquesNaturales"
- "ParquesNaturales.Limites"
- "ParquesNaturales.ZonasPerifericas"

Source

<https://dieghernan.github.io/leaflet-providersESP/> leaflet plugin, v1.3.3.

See Also

Other datasets: [esp_codelist](#), [esp_munic.sf](#), [esp_nuts.sf](#), [pobmun19](#)

Other imagery utilities: [addProviderEspTiles\(\)](#), [esp_getTiles\(\)](#), [esp_make_provider\(\)](#)

Examples

```
data("esp_tiles_providers")
# Get a single provider

single <- esp_tiles_providers[["IGNBase.Todo"]]
single$static

single$leaflet
```

pobmun19

Population by municipality (2019)

Description

Population by municipality (2019)

Format

An example data frame with 8,131 rows containing the population data by municipality in Spain (2019).

cpro INE code of the province.

provincia name of the province.

cmun INE code of the municipality.

name Name of the municipality.

pob19 Overall population (2019)

men Men population (2019)

women Women population (2019)

Source

INE: Instituto Nacional de Estadistica <https://www.ine.es/>

See Also

Other datasets: [esp_codelist](#), [esp_munic.sf](#), [esp_nuts.sf](#), [esp_tiles_providers](#)

Examples

```
data("pobmun19")
```

Index

- * **Canary Islands**
 - esp_get_can_box, 13
 - esp_move_can, 60
- * **cache utilities**
 - esp_clear_cache, 5
 - esp_detect_cache_dir, 8
 - esp_set_cache_dir, 65
- * **datasets**
 - esp_codelist, 6
 - esp_munic.sf, 61
 - esp_nuts.sf, 63
 - esp_tiles_providers, 66
 - pobmun19, 70
- * **dictionary**
 - esp_codelist, 6
 - esp_dict_region_code, 8
- * **grids**
 - esp_get_grid_BDN, 29
 - esp_get_grid_EEA, 30
 - esp_get_grid_ESDAC, 32
 - esp_get_grid_MTN, 34
- * **helper**
 - esp_check_access, 4
 - esp_move_can, 60
- * **imageries utilities**
 - addProviderEspTiles, 3
 - esp_getTiles, 10
 - esp_make_provider, 59
 - esp_tiles_providers, 66
- * **infrastructure**
 - esp_get_railway, 50
 - esp_get_roads, 55
- * **municipalities**
 - esp_get_capimun, 16
 - esp_get_munic, 41
 - esp_munic.sf, 61
- * **natural**
 - esp_get_hydrobasin, 36
 - esp_get_hypsobath, 38
- * **nuts**
 - esp_get_nuts, 44
 - esp_nuts.sf, 63
- * **political**
 - esp_codelist, 6
 - esp_get_can_box, 13
 - esp_get_capimun, 16
 - esp_get_ccaa, 19
 - esp_get_comarca, 22
 - esp_get_country, 25
 - esp_get_gridmap, 27
 - esp_get_munic, 41
 - esp_get_nuts, 44
 - esp_get_prov, 47
 - esp_get_simpl_prov, 57
- addProviderEspTiles, 3, 12, 59, 69
- addProviderEspTiles(), 14, 18, 21, 24, 26, 43, 46, 49, 56, 66
- base::regex(), 43
- base::tempdir(), 65
- esp_check_access, 4, 61
- esp_clear_cache, 5, 8, 66
- esp_codelist, 6, 9, 15, 17, 18, 20, 21, 23, 24, 26, 27, 42, 43, 46, 48, 49, 57, 58, 62, 64, 69, 70
- esp_detect_cache_dir, 5, 8, 66
- esp_dict_region_code, 7, 8
- esp_dict_region_code(), 9, 45, 46
- esp_dict_translate
 - (esp_dict_region_code), 8
- esp_dict_translate(), 9
- esp_get_can_box, 7, 13, 18, 21, 24, 26, 27, 43, 46, 49, 58, 61
- esp_get_can_box(), 14
- esp_get_can_provinces
 - (esp_get_can_box), 13

esp_get_can_provinces(), 14
 esp_get_capimun, 7, 15, 16, 21, 24, 26, 27,
 43, 46, 49, 58, 62
 esp_get_ccaa, 7, 15, 18, 19, 24, 26, 27, 43,
 46, 49, 58
 esp_get_ccaa(), 19, 20, 29, 30
 esp_get_ccaa_siane (esp_get_ccaa), 19
 esp_get_ccaa_siane(), 19, 20
 esp_get_comarca, 7, 15, 18, 21, 22, 26, 27,
 43, 46, 49, 58
 esp_get_country, 7, 15, 18, 21, 24, 25, 27,
 43, 46, 49, 58
 esp_get_grid_BDN, 29, 31, 33, 35
 esp_get_grid_BDN(), 29
 esp_get_grid_BDN_ccaa
 (esp_get_grid_BDN), 29
 esp_get_grid_BDN_ccaa(), 29
 esp_get_grid_ccaa (esp_get_gridmap), 27
 esp_get_grid_EEA, 30, 30, 33, 35
 esp_get_grid_ESDAC, 30, 31, 32, 35
 esp_get_grid_MTN, 30, 31, 33, 34
 esp_get_grid_prov (esp_get_gridmap), 27
 esp_get_gridmap, 7, 15, 18, 21, 24, 26, 27,
 43, 46, 49, 58
 esp_get_hex_ccaa (esp_get_gridmap), 27
 esp_get_hex_ccaa(), 58
 esp_get_hex_prov (esp_get_gridmap), 27
 esp_get_hex_prov(), 58
 esp_get_hydrobasin, 36, 39, 53
 esp_get_hypsobath, 37, 38, 53
 esp_get_munic, 7, 15, 18, 21, 24, 26, 27, 41,
 46, 49, 58, 62
 esp_get_munic(), 16, 41, 42, 62
 esp_get_munic_siane (esp_get_munic), 41
 esp_get_munic_siane(), 41, 42
 esp_get_nuts, 7, 15, 18, 20, 21, 24–27, 43,
 44, 48, 49, 58, 64
 esp_get_nuts(), 14, 20, 48
 esp_get_prov, 7, 15, 18, 21, 24, 26, 27, 43,
 46, 47, 58
 esp_get_prov(), 47, 48
 esp_get_prov_siane (esp_get_prov), 47
 esp_get_prov_siane(), 47–49
 esp_get_railway, 50, 56
 esp_get_rivers, 37, 39, 52
 esp_get_roads, 52, 55
 esp_get_simpl_ccaa
 (esp_get_simpl_prov), 57
 esp_get_simpl_prov, 7, 15, 18, 21, 24, 26,
 27, 43, 46, 49, 57
 esp_getTiles, 4, 10, 59, 69
 esp_getTiles(), 14, 18, 21, 24, 26, 43, 46,
 49, 56, 59, 66
 esp_make_provider, 4, 12, 59, 69
 esp_make_provider(), 11
 esp_move_can, 4, 15, 60
 esp_move_can(), 14, 18, 21, 24, 26, 43, 46,
 49, 56
 esp_munic_sf, 7, 18, 43, 61, 64, 69, 70
 esp_nuts_sf, 7, 46, 62, 63, 69, 70
 esp_set_cache_dir, 5, 8, 65
 esp_set_cache_dir(), 8, 12, 18, 20, 23, 26,
 30, 31, 33, 35, 37, 39, 43, 45, 49, 51,
 56, 58
 esp_tiles_providers, 3, 4, 7, 12, 59, 62, 64,
 66, 70
 esp_tiles_providers(), 11
 giscoR::gisco_attributions(), 19, 41, 46,
 47
 giscoR::gisco_check_access(), 4
 giscoR::gisco_get_communies(), 42
 giscoR::gisco_get_lau(), 42, 43
 giscoR::gisco_get_nuts(), 46
 leaflet::addTiles(), 3, 4
 leaflet::leaflet(), 3, 4
 leaflet::providerTileOptions(), 3, 4
 leaflet::tileOptions(), 4
 pobmun19, 7, 62, 64, 69, 70
 providerEspTileOptions
 (addProviderEspTiles), 3
 providerEspTileOptions(), 3
 rappdirs::user_config_dir(), 66
 regex, 17, 23, 42, 53
 sf::st_transform(), 27
 terra::rast(), 12